		[188] 7.4	
C		5.5] .22 (X) (90) 3.5	
В			These devices sl thickness and w
			mounting to a su
_		HOUSING MATERIALS BODY: EPOXY COATED DIE CAST ALUMINUM GASKET: THERMOPLASTIC ELASTON HANDLE: POLYAMIDE	VOLTS: AMPS: /IER SCCR:
		BODY: EPOXY COATED DIE CAST ALUMINUM GASKET: THERMOPLASTIC ELASTOM HANDLE: POLYAMIDE LEVERS: STAINLESS STEEL	VOLTS: AMPS: /IER SCCR: NEMA/UL MOUNTING
		BODY: EPOXY COATED DIE CAST ALUMINUM GASKET: THERMOPLASTIC ELASTON HANDLE: POLYAMIDE LEVERS: STAINLESS STEEL OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140°	VOLTS: AMPS: /IER SCCR: NEMA/UL MOUNTING ? F)) MOUNTING
		BODY: EPOXY COATED DIE CAST ALUMINUM GASKET: THERMOPLASTIC ELASTON HANDLE: POLYAMIDE LEVERS: STAINLESS STEEL OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° MOUNTING KIT ORDERED SEPARATELY CONTAINS M5x0.8 SS SCREW, NYLON WASHER,	VOLTS: AMPS: AMPS: AMPS: AER SCCR: NEMA/UL MOUNTING CIFIED: DRAWN BY HES DRAWN DATE ORAWN DATE
		BODY: EPOXY COATED DIE CAST ALUMINUM GASKET: THERMOPLASTIC ELASTON HANDLE: POLYAMIDE LEVERS: STAINLESS STEEL OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° MOUNTING KIT ORDERED SEPARATELY CONTAINS M5x0.8 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M5 NUT	VOLTS: AMPS: AMPS: MER SCCR: NEMA/UL MOUNTING CIFIED: DRAWN BY IES DRAWN DATE 07.
		BODY: EPOXY COATED DIE CAST ALUMINUM GASKET: THERMOPLASTIC ELASTON HANDLE: POLYAMIDE EVERS: LEVERS: STAINLESS STEEL OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° C (+14° F / +140° C (+14° F / +140° C (+14° F / +140° DIMENSIONS ARE IN INC SEPARATELY CONTAINS M5x0.8 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M5 NUT UNLESS OTHERWISE SPL DIMENSIONS ARE IN INC SIR2 PROPRIETARY AND CONFIDENTIAL Image: Control of the control of	VOLTS: AMPS: AMPS: AMPS: MEMA/UL MOUNTING CIFIED: DRAWN DATE CHECKED BY
S	TANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED ONN. TYPE EXTERIOR INTERIOR	BODY: EPOXY COATED DIE CAST ALUMINUM GASKET: THERMOPLASTIC ELASTON HANDLE: POLYAMIDE LEVERS: STAINLESS STEEL OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° MOUNTING KIT ORDERED SEPARATELY CONTAINS M5x0.8 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M5 NUT P/N: D-PIC-MT-M5 PROPRIETARY AND CONFIDENTIAL	VOLTS: AMPS: AMPS: AMPS: AMPS: AMPA/UL MOUNTING TF)) MOUNTING CIFIED: DRAWN BY HES DRAWN DATE CHECK DATE O7. CHECK DATE O7. CH

8	7	6	5	4	3		2		1	7
·	[125] 4.9 [112] 4.4 [112]				_ [188] 7.4		Cala		475" [10]	D
67] 2.6			5.5]				to 0.7	e gland for 0 '87'' [20] cabl	.473 [12] e.	С
			9.22 4X)		[90] 3.5		juate spacing prov nat is clean, flat an		th and	В
					HOUSING MATERIALS EPOXY COATED DIE CAST	VOLTS:	PIC RATING	SS/SPECIFICATIONS		
				BODY: GASKET:	ALUMINUM THERMOPLASTIC ELASTOMER	AMPS: SCCR:		5A 0.2kA		
				HANDLE: LEVERS:	POLYAMIDE STAINLESS STEEL	NEMA/UL EN MOUNTING SCR		4, 4X, 12 IP65 M5 (10-32) (304		
			OPERATING TEMPER		°C / +60° C (+14° F / +140° F)) MOUNTING SCR				
			MOUNTING KIT ORDERE SEPARATELY CONTAINS		CULUS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES AND [MM]	D: DRAWN BY GO DRAWN DATE 07/26/202 CHECKED BY DCG	MEN TITLE:	ICOM CORPO	ORATION	_
			M5x0.8 SS SCREW, NYLC SPLIT LOCKWASHER AN P/N: D-PIC-MT-M5		LISTED ENCL. ACC. 5JR2	CHECK DATE 07/26/202	DUP	K;2 RJ;5A RESET;SU	IRF MNT 32	A
			PROPRIETARY AND CONFIDENTIAL			COMMENTS:				
	SURATIONS UNLESS OTHERW		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY		MATERIAL		SIZE DWG	. NO. DP-2RJ45-5R-P3	REV	
TYPE	EXTERIOR INTERI		REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS		FINISH		B			
8	CAT. 6 JACK CAT. 6	JACK	PROHIBITED.	Å	DO NOT SCALE DRAWING		SCALE: 2:3	WEIGHT:	SHEET 1 OF 1	
0	/	O	Э	4	3		2		I	