	8	7		6	5	÷	4	3		2		1	
D			[120 5.0						41				D
					D [91] 3.6								
С													С
													-
В		PANEL CU [88] 3.46	_ _	[4.5] - ∅.18 4X					These devices shall be thickness and with ade mounting to a surface t	quate spacing provid hat is clean, flat and	ed. Seal rating is based smooth.	1 on	В
	\bigcirc	T T							VOLTS:	PIC RA IINGS	/SPECIFICATION	5	
							HOUSING	MATERIALS	AMPS:		6A		
		[76]	[65]]		BODY:		COATED DIE CAST	SCCR:	60520-	0.2kA	DCE	
		2.99	2.56			GASKE	ALUMINU	JM)PLASTIC ELASTOMER	NEMA/UL EN MOUNTING SCR		4, 4X, 12 II M4 (8-32) (304	265 4 or 316SS for 4	4X)
				-		HANDL	POLYAN	1IDE	MOUNTING SCR	EW TORQUE:	1.2~1.8N-m (0	0.9~1.3 Lb-Ft)	
								SS STEEL	INCOMING POW		0.5 ~ 4.0 sq n 10 ~ 11 mm	nm / 20-12AWC	3
	\bigcirc				MOUNTING KIT O			C (+14° F / +140° F) UNLESS OTHERWISE SPECIFIE					
	I				SEPARATELY COM	NTAINS		US DIMENSIONS ARE IN INCHES TOLERANCES:	DRAWN DATE 08/02/202	1	COM CORP	UKAIION	
A		[110] 4.33			M4x0.7 SS SCREW SPLIT LOCKWASH P/N: D-PIC-MT		LISTED ENCL. ACC.	FRACIIONAL±1/64	5° CHECKED BY DCG CHECK DATE 08/02/202	TITLE: DUP	K; 2- RJ45; 6/	amp sz 32	A
					PROPRIETARY AND CONFIDE	NTIAL	5JR2						
STAN		URATIONS LINE ESS	OTHERWISE NOTED		THE INFORMATION CONTAINED I DRAWING IS THE SOLE PROPERTY	N THIS		MATERIAL	COMMENTS:	SIZE DWG. 1	NO.		REV
CONN		EXTERIOR	INTERIOR		MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A	A WHOLE		FINISH		B	DP-2RJ45-6	R-32	D
RJ45		CAT. 6 JACK	CAT. 6 JACK		WITHOUT THE WRITTEN PERMISSIC MENCOM CORPORATION IS PROHIBITED.			DO NOT SCALE DRAWING	_		WEIGHT:	SHEET 1	
L	8	7		6	5	1 1	4	3		2		1	
					-			-				-	



