



These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK

		PIC RATINGS/SPECIFICATIONS				
		VOLTS:	250V			
		AMPS:	3A			
		SCCR:	0.2kA			
		NEMA/UL   EN 60529:	4, 4X, 12   IP65			
		MOUNTING SCREW SIZE:	M5 (10-32) (304 or 316SS for 4X)			
		MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)			
		INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG			
HOUSING MATERIALS						
BODY:	EPOXY COATED DIE CAST ALUMINUM					
GASKET:	THERMOPLASTIC ELASTOMER					
HANDLE:	POLYAMIDE					
LEVERS:	STAINLESS STEEL					
OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° F ))						
<div>MOUNTING KIT ORDERED SEPARATELY CONTAINS M5x0.8 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M5 NUT</div> <div>P/N: D-PIC-MT-M5</div> <div>PROPRIETARY AND CONFIDENTIAL</div> <div>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.</div>		<div>UNLESS OTHERWISE SPECIFIED:</div> <div>DIMENSIONS ARE IN INCHES AND [MM]</div> <div>MATERIAL</div> <div>FINISH</div> <div>DO NOT SCALE DRAWING</div>	DRAWN BY	DG	<div>MENCOM CORPORATION</div> <div>TITLE:</div> <div>DUPX;2 RJ;3A RESET;SURF MNT 32</div>	
			DRAWN DATE	07/08/2021		
			CHECKED BY	DCG		
			CHECK DATE	07/08/2021		
		COMMENTS:				
				SIZE	DWG. NO.	REV
				B	DP-2RJ45-R-P32	C
				SCALE: 2:3		SHEET 1 OF 1
				WEIGHT:		