


These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS	
BODY:	EPOXY COATED DIE CAST ALUMINUM	VOLTS:	125V
GASKET:	THERMOPLASTIC ELASTOMER	AMPS:	3A
HANDLE:	POLYAMIDE	SCCR:	10kA
LEVERS:	STAINLESS STEEL	NEMA/UL EN 60529:	4, 4X, 12 IP65
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]		MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
		MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)
		INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
		WIRE STRIP LENGTH:	10 ~ 11 mm
 LISTED ENCL. ACC. 5JR2		DRAWN BY	DCG
		DRAWN DATE	05/15/2019
		CHECKED BY	GO
		CHECK DATE	05/15/2019
MATERIAL		COMMENTS:	
FINISH		MENCOM CORPORATION	
DO NOT SCALE DRAWING		TITLE: DPLX; DB9; DB25; 3A; 32	
SIZE		DWG. NO. DP-DB9-DB25-R-32	
WEIGHT:		REV D	
SHEET 1 OF 1		SCALE: 3:4	

MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.