



| STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED | | |
|--|-------------|-------------|
| CONN. TYPE | EXTERIOR | INTERIOR |
| RJ45 | CAT. 6 JACK | CAT. 6 JACK |
| ALL D-SUBS | FEMALE | MALE |

MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT



| HOUSING MATERIALS | |
|-------------------|--------------------------------|
| BODY: | EPOXY COATED DIE CAST ALUMINUM |
| GASKET: | THERMOPLASTIC ELASTOMER |
| HANDLE: | POLYAMIDE |
| LEVERS: | STAINLESS STEEL |

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
AND [MM]

| | | | | | |
|----------------------------|------------|---------------------------------|---|-------------------|--------------|
| PIC RATINGS/SPECIFICATIONS | | | | | |
| VOLTS: | | 125V | | | |
| AMPS: | | 5A | | | |
| SCCR: | | 0.2kA | | | |
| NEMA/UL EN 60529: | | 4, 4X, 12 IP65 | | | |
| MOUNTING SCREW SIZE: | | M4 (8-32) (304 or 316SS for 4X) | | | |
| MOUNTING SCREW TORQUE: | | 1.2~1.8N-m (0.9~1.3 Lb-Ft) | | | |
| INCOMING POWER WIRE SIZE: | | 0.5 ~ 4.0 sq mm / 20-12AWG | | | |
| WIRE STRIP LENGTH: | | 10 ~ 11 mm | | | |
| D: | DRAWN BY | DCG | MENCOM CORPORATION TITLE: DPLX; DB9; RJ45; 5A; 32 | | |
| | DRAWN DATE | 09/22/2016 | | | |
| | CHECKED BY | | | | |
| | CHECK DATE | | | | |
| | | | | | |
| | COMMENTS: | | SIZE | DWG. NO. | REV |
| | | | B | DP-DB9-RJ45-5R-32 | C |
| | | | SCALE: 2:3 | WEIGHT: | SHEET 1 OF 1 |