



A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PART NUMBER	LENGTH "L"	PIC RATINGS/SPECIFICATIONS	
DP1-RJ45-2USB-01-R-32	1 FOOT	VOLTS:	125V
DP1-RJ45-2USB-03-R-32	3 FEET	AMPS:	15A
DP1-RJ45-2USB-06-R-32	6 FEET	SCCR:	10kA
DP1-RJ45-2USB-10-R-32	10 FEET		
HOUSING MATERIALS		NEMA/UL EN 60529:	4, 4X, 12 IP65
BODY:	EPOXY COATED DIE CAST ALUMINUM	MOUNTING SCREW SIZE:	M6 (1/4-20) (304 or 316SS for 4X)
GASKET:	THERMOPLASTIC ELASTOMER	MOUNTING SCREW TORQUE:	3.0~3.6N-m (2.2~2.7 Lb-Ft)
HANDLE:	STAINLESS STEEL	INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
		WIRE STRIP LENGTH:	10 ~ 11 mm

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 5e JACK	CAT 5e JACK
ALL D-SUBS	FEMALE	MALE
USB 2.0	TYPE A FEMALE	TYPE A MALE

MOUNTING KIT ORDERED SEPARATELY CONTAINS M6x1 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M6 NUT
P/N: D-PIC48-MT



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	
DRAWN BY	DCG
DRAWN DATE	09/20/2017
CHECKED BY	JJH
CHECK DATE	09/20/2017
COMMENTS:	
MATERIAL	
FINISH	
DO NOT SCALE DRAWING	

MENCOM CORPORATION		
TITLE: DP;HD15;RJ45;4USB;SZ48		
SIZE B	DWG. NO. DP-DDB15-RJ45-4USB-ZZ-48LS	REV B
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1