

I	2	2			1		
							D
		ALE l PE A				-	
"							С
		PART	NUM	BER	LENC	GTH "L"	-
DP-MDB9-RJ45-USB-3-R-32 3 FEET DP-MDB9-RJ45-USB-6-R-32 6 FEET DP-MDB9-RJ45-USB-10-R-32 10 FEET icces shall be mounted on enclosures having adequate strength and and with adequate spacing provided. Seal rating is based on to a surface that is clean, flat and smooth.							В
				ECIFICATIONS			
				125V 3A 0.2kA			
JL EN 60529: ING SCREW SIZE: ING SCREW TORQUE: NG POWER WIRE SIZE: STRIP LENGTH:				4, 4X, 12 IP65 M4 (8-32) (304 or 316SS for 4X) 1.2~1.8N-m (0.9~1.3 Lb-Ft) 0.5 ~ 4.0 sq mm / 20-12AWG 10 ~ 11 mm			
DCG 07/13/2021	MENCOM CORPORATION						
APR 07/13/2021	TITLE: DPLX; MDB9; RJ45; USB PCBL;3A; 32						A
size dwg. no. B DP-MD				B9-RJ45-USB-ZZ-	R-32	REV B	
	SCAL	E: 2:3	WE	IGHT:		1 OF 1	
	2				1		