



These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS		
BODY:	EPOXY COATED DIE CAST ALUMINUM	VOLTS:	125V	
GASKET:	THERMOPLASTIC ELASTOMER	AMPS:	3A	
HANDLE:	POLYAMIDE	SCCR:	0.2kA	
LEVERS:	STAINLESS STEEL	NEMA/UL EN 60529:	4, 4X, 12 IP65	
OPERATING TEMPERATURE: (-20°C / +60° C (-4° F / +140° F))		MOUNTING SCREW SIZE:	M5 (10-32) (304 or 316SS for 4X)	
MOUNTING KIT ORDERED SEPARATELY CONTAINS M5x0.8 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M5 NUT P/N: D-PIC-MT-M5		MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)	
		UNLESS OTHERWISE SPECIFIED: DRAWN BY ADM DIMENSIONS ARE IN INCHES AND [MM] DRAWN DATE 07/13/2021		
		CHECKED BY DCG CHECK DATE 07/13/2021		
		COMMENTS:		
UL LISTED ENCL. ACC. 5JR2		MENCOM CORPORATION TITLE: DPLX; 3A; 32 SRF MT		
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.				
MATERIAL FINISH		SIZE B DWG. NO. DP-R-P32	REV B	
DO NOT SCALE DRAWING		SCALE: 2:3	WEIGHT:	SHEET 1 OF 1