8		7	6	5	4		3		2		1	
			FEMALE	USB 3.0						ALE USB 3.0 PE A		
	PANEL CUT [88] 3.46	out 	TYPE A [4.5] — Ø.18					These devices sha thickness and with		-03-R-32 -06-R-32 osures having adequate stre ovided. Seal rating is based	0	-
_	[76] 2.99	[6. 2.			BODY: GASKET: HANDLE: LEVERS:	ALUMINUM THERMOP POLYAMIE STAINLES	DATED DIE CAST M PLASTIC ELASTOMEI DE SS STEEL	R MOUNTING S MOUNTING S INCOMING P	EN 60529: SCREW SIZE: SCREW TORQUE: POWER WIRE SIZ	:: 1.2~1.8N-m (0 ZE: 0.5 ~ 4.0 sq m	P65 4 or 316SS for 4	
				OPERATING TEMPERATURE: (-1 MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT P/N: D-PIC-MT			(+14° F / +140° F UNLESS OTHERWISE SPECIFI DIMENSIONS ARE IN INCHES AND [MM]	IED: DRAWN BY DO DRAWN DATE 07/08 CHECKED BY DO	LENGTH: 10 ~ 11 mm CG MENCOM CORPOR/ 8/2021 TITLE: 9/2021 DPLX; RJ45; USB 3.0 ZZ; 3A; 3			Ν
				PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS			MATERIAL	COMMENTS:	SIZE DWG		r	REV



