

For power connector, crimp terminals are supplied for hot and neutral connection. Ground wire supplied with an M3 ring terminal applied to end of 6" ground lead.

4

3

5

| | | | | receptacle | • | vided, a Mark | | fuse or circuit breaker rate be provided to indicate the | | | |
|--|---------|----------------------------|---|----------------------|------------------------------|---|---------------------------------|---|---------|------|---|
| | | | | | | These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth. | | | | | |
| | | PIC RATINGS/SPECIFICATIONS | | | | | | | | | |
| | | | | VOLTS: AMPS: | | | | 125V 15A | | | |
| HOUSING MATERIAL | | | TERIALS | SCCR: | | | | 10kA | | | _ |
| | BODY: | EPOXY COATED DIE CAST | | NEMA/UL EN 60529: | | | | 4, 4X, 12 IP65 | | | |
| BODT. | | ALUMINUM | | MOUNTING SCREW SIZE: | | | M4 (8-32) (304 or 316SS for 4X) | | | | |
| | GASKET: | THERMOPL | MOUNTING SCREW TORQUE: | | | 1.2~1.8N-m (0.9~1.3 Lb-Ft) | | | | | |
| | HANDLE: | POLYAMIDE | INCOMING POWER WIRE SIZE: | | | | 0.5 ~ 4.0 sq mm / 20-12AWG | | | | |
| SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT | | | STEEL | WIRE S | WIRE STRIP LENGTH:10 ~ 11 mm | | | | | | |
| | | | UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM] | DRAWN BY | DCG | MENCOM CORPORATION | | | | | |
| | | | | DRAWN DATE | 06/05/2019 | | | | | | |
| | | | | CHECKED BY | DCG | TITLE: SMPLX; 2-9 PINS; RJ45; SZ 32 | | | | | |
| | | | | CHECK DATE | 06/05/2019 | | | | | A | |
| P/N: D-PIC-MT | | ENCL. ACC. 5JR2 | | | | J | | , Z-7 T INS, NJ40 | , 32 32 | | |
| PROPRIETARY AND CONFIDENTIAL | | | | | | | | | | | |
| THE INFORMATION CONTAINED IN THIS | | | MATERIAL | COMMENTS: | | SIZE DWG. NO. REV | | | | REV | |
| DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY | | | FINISH | | | | | | B | | |
| REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF | | | | | | D | | 1 2007 10 10 02 | | D | |
| MENCOM CORPORATION IS PROHIBITED. | | | DO NOT SCALE DRAWING | | | SCALE: 2:3 | WE | IGHT: | SHEET 1 | OF 1 | |
| 4 | | | | | | | | | | | 1 |

3

4

8

ALL D-SUBS

RJ45

D

С

В

А

CAT 6 JACK 7

FEMALE

6

CAT 6 JACK

MALE

5

2

23 .9

(0)



D

С

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked le in the and use. When a fuse as size with breaker retail less th

| DCG | MENCOM CORPORATION | | | | | | | | |
|------------|------------------------------|------|---------|--------------|--------------|-----------------|---|--|--|
| 06/05/2019 | | | | | | | | | |
| DCG | TITLE | : | | | | | | | |
| 06/05/2019 | SMPLX; 2-9 PINS; RJ45; SZ 32 | | | | | | | | |
| | size B | DWG. | | 2DB9-RJ45-32 | 2 | rev B | _ | | |
| | SCALE: 2:3 | | WEIGHT: | | SHEET 1 OF 1 | | | | |
| | 2 | | | | 1 | | | | |