		7	6	5	5	4		3		2		1	
-	[126] 5.0				/GA) CONFIGURE / FEMALE INTERIOF	R _ [(63]						D
							}P						
			[92] 3.6										С
-				B 3.0 TYPE A FI RIOR / FEMAL									-
	PANEL CUTO	JUT							These devices shall be m thickness and with adequ mounting to a surface that	uate spacing provi	ided. Seal rating is base		В
	[88]	JUT	[4.5]						thickness and with adequ	uate spacing provi at is clean, flat an	ided. Seal rating is base	ed on	В
		JUT	[4.5] / Ø.18						thickness and with adeque mounting to a surface that VOLTS:	uate spacing provi at is clean, flat an	ided. Seal rating is base d smooth. S/SPECIFICATION 125V	ed on	В
	[88]		[4.5]				HOUSING MATER	RIALS	thickness and with adeque mounting to a surface that VOLTS: AMPS:	uate spacing provi at is clean, flat an	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A	ed on	B
0	[88]		[4.5] / Ø.18			BODY:	EPOXY COATED ALUMINUM	RIALS D DIE CAST	thickness and with adeque mounting to a surface that VOLTS:	uate spacing provi at is clean, flat an PIC RATING	ided. Seal rating is base d smooth. S/SPECIFICATION 125V	ed on NS	B
0	[88]		[4.5] / Ø.18			GASKET:	EPOXY COATED ALUMINUM THERMOPLAST	RIALS D DIE CAST	thickness and with adeque mounting to a surface that VOLTS: AMPS: SCCR: NEMA/UL EN 6 MOUNTING SCRE	uate spacing provi at is clean, flat an PIC RATING 0529: W SIZE:	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) (30	IP65 04 or 316SS for 4	B
0	[88]	TUC	[4.5] / Ø.18				EPOXY COATED ALUMINUM	RIALS D DIE CAST TIC ELASTOMER	thickness and with adeque mounting to a surface that VOLTS: AMPS: SCCR: NEMA/UL EN 6 MOUNTING SCRE MOUNTING SCRE	Date spacing provi at is clean, flat an PIC RATING 0529: W SIZE: W SIZE:	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) (30 1.2~1.8N-m (ed on NS IP65 04 or 316SS for 4 (0.9~1.3 Lb-Ft)	
0	[88] 3.46 [76]	/	[4.5] Ø.18 4X [65]			GASKET: HANDLE: LEVERS:	EPOXY COATED ALUMINUM THERMOPLAST POLYAMIDE STAINLESS STE	RIALS D DIE CAST TIC ELASTOMER EEL	thickness and with adeque mounting to a surface that VOLTS: AMPS: SCCR: NEMA/UL EN 6 MOUNTING SCRE MOUNTING SCRE INCOMING POWE	ate spacing provi at is clean, flat an PIC RATING 0529: W SIZE: W SIZE: R WIRE SIZE	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) (30 1.2~1.8N-m (IP65 04 or 316SS for 4 (0.9~1.3 Lb-Ft) mm / 20-12AWG	
0	[88] 3.46	/	[4.5] Ø.18 4X		OPERATING TEMPE MOUNTING KIT ORDE	GASKET: HANDLE: LEVERS: ERATURE: (-10	EPOXY COATEL ALUMINUM THERMOPLAST POLYAMIDE STAINLESS STE 0°C / +60° C (+14	RIALS D DIE CAST FIC ELASTOMER EEL ° F / +140° F)) ESS OTHERWISE SPECIFIED:	thickness and with adeque mounting to a surface that VOLTS: AMPS: SCCR: NEMA/UL EN 6 MOUNTING SCRE MOUNTING SCRE MOUNTING SCRE INCOMING POWE WIRE STRIP LENC	ate spacing provi at is clean, flat an PIC RATING 0529: W SIZE: W SIZE: W TORQUE: R WIRE SIZE STH:	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) (30 1.2~1.8N-m (0.5 ~ 4.0 sq 10 ~ 11 mm	ed on NS IP65 04 or 316SS for 4 (0.9~1.3 Lb-Ft) mm / 20-12AWG	3
0	[88] 3.46 [76]	/	[4.5] Ø.18 4X [65]		OPERATING TEMPE MOUNTING KIT ORDE SEPARATELY CONTAIL	GASKET: HANDLE: LEVERS: ERATURE: (-10 RED NS	EPOXY COATEL ALUMINUM THERMOPLAST POLYAMIDE STAINLESS STE 0°C / +60° C (+14	RIALS D DIE CAST FIC ELASTOMER EEL ° F / +140° F)) ESS OTHERWISE SPECIFIED:	thickness and with adeque mounting to a surface that VOLTS: AMPS: SCCR: NEMA/UL EN 6 MOUNTING SCRE MOUNTING SCRE INCOMING POWE WIRE STRIP LENC DRAWN BY DCG DRAWN DATE 07/09/2021	ate spacing provi at is clean, flat an PIC RATING 0529: W SIZE: W SIZE: W TORQUE: R WIRE SIZE STH:	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) (30 1.2~1.8N-m (.: 0.5 ~ 4.0 sq	ed on NS IP65 04 or 316SS for 4 (0.9~1.3 Lb-Ft) mm / 20-12AWG	3
0	[88] 3.46 [76] 2.99	/	[4.5] Ø.18 4X [65]		OPERATING TEMPE MOUNTING KIT ORDE	GASKET: HANDLE: LEVERS: ERATURE: (-10 RED NS YLON WASHER,	EPOXY COATEL ALUMINUM THERMOPLAST POLYAMIDE STAINLESS STE 0°C / +60° C (+14	RIALS D DIE CAST FIC ELASTOMER EEL ° F / +140° F)) ESS OTHERWISE SPECIFIED:	thickness and with adeque mounting to a surface that VOLTS: AMPS: SCCR: NEMA/UL EN 6 MOUNTING SCRE MOUNTING SCRE INCOMING POWE WIRE STRIP LENC DRAWN BY DCG DRAWN DATE 07/09/2021	ate spacing provi at is clean, flat an PIC RATING 0529: W SIZE: W TORQUE: R WIRE SIZE STH: MEN TITLE:	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) (30 1.2~1.8N-m (0.5 ~ 4.0 sq 10 ~ 11 mm	IP65 04 or 316SS for 4 (0.9~1.3 Lb-Ft) mm / 20-12AWG	3
	[88] 3.46 [76] 2.99 [110]	/	[4.5] Ø.18 4X [65]		OPERATING TEMPE MOUNTING KIT ORDE SEPARATELY CONTAIL M4x0.7 SS SCREW, NY SPLIT LOCKWASHER A P/N: D-PIC-MT PROPRIETARY AND CONFIDENTIAL	GASKET: HANDLE: LEVERS: ERATURE: (-10 RED NS YLON WASHER,	EPOXY COATEL ALUMINUM THERMOPLAST POLYAMIDE STAINLESS STE O°C / +60° C (+14 O°C / +60° C (+14 UNLE LISTED ENCL. ACC. 5JR2	RIALS D DIE CAST TIC ELASTOMER EEL ° F / +140° F)) ESS OTHERWISE SPECIFIED: ENSIONS ARE IN INCHES [MM]	thickness and with adeque mounting to a surface that VOLTS: AMPS: SCCR: NEMA/UL EN 6 MOUNTING SCRE MOUNTING SCRE INCOMING POWE WIRE STRIP LENC DRAWN DATE 07/09/2021 CHECKED BY DCG	ate spacing provi at is clean, flat an PIC RATING WSIZE: W TORQUE: R WIRE SIZE STH: MEN TITLE: SI	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) (30 1.2~1.8N-m (: 0.5 ~ 4.0 sq 10 ~ 11 mm COM COR	IP65 04 or 316SS for 4 (0.9~1.3 Lb-Ft) mm / 20-12AWG PORATION	S N A
	[88] 3.46 [76] 2.99	/	[4.5] Ø.18 4X [65]		OPERATING TEMPE MOUNTING KIT ORDE SEPARATELY CONTAIL M4x0.7 SS SCREW, NY SPLIT LOCKWASHER A P/N: D-PIC-MT PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOL WITHOUT THE WRITTEN PERMISSION OF	GASKET: HANDLE: LEVERS: ERATURE: (-10 RED NS YLON WASHER, AND M4 NUT	EPOXY COATEL ALUMINUM THERMOPLAST POLYAMIDE STAINLESS STE O°C / +60° C (+14 COUCLISTED ENCLACC.	RIALS D DIE CAST FIC ELASTOMER EEL * F / +140° F)) ESS OTHERWISE SPECIFIED: ENSIONS ARE IN INCHES [MM]	thickness and with adeque mounting to a surface that VOLTS: AMPS: SCCR: NEMA/UL EN 6 MOUNTING SCRE MOUNTING SCRE INCOMING POWE WIRE STRIP LENC DRAWN BY DCG DRAWN DATE 07/09/2021 CHECK DATE 07/13/2021	ate spacing provi at is clean, flat an PIC RATING 0529: W SIZE: W TORQUE: R WIRE SIZE STH: MEN TITLE: SIZE DWG.	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) (30 1.2~1.8N-m (: 0.5 ~ 4.0 sq 10 ~ 11 mm COM COR	ed on NS IP65 04 or 316SS for 4 (0.9~1.3 Lb-Ft) mm / 20-12AWG PORATION JSB; 3A; 32	s N
	[88] 3.46 [76] 2.99 [110]	/	[4.5] Ø.18 4X [65]		OPERATING TEMPE MOUNTING KIT ORDE SEPARATELY CONTAIL M4x0.7 SS SCREW, NY SPLIT LOCKWASHER A P/N: D-PIC-MT PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOL	GASKET: HANDLE: LEVERS: ERATURE: (-10 RED NS YLON WASHER, AND M4 NUT	EPOXY COATEL ALUMINUM THERMOPLAST POLYAMIDE STAINLESS STE O°C / +60° C (+14 O°C / +60° C (+14 UNLE LISTED ENCL. ACC. SJR2 MATER FINISH	RIALS D DIE CAST FIC ELASTOMER EEL * F / +140° F)) ESS OTHERWISE SPECIFIED: ENSIONS ARE IN INCHES [MM]	thickness and with adeque mounting to a surface that VOLTS: AMPS: SCCR: NEMA/UL EN 6 MOUNTING SCRE MOUNTING SCRE INCOMING POWE WIRE STRIP LENC DRAWN BY DCG DRAWN DATE 07/09/2021 CHECK DATE 07/13/2021	ate spacing provi at is clean, flat an PIC RATING 0529: W SIZE: W TORQUE: R WIRE SIZE STH: MEN TITLE: SI	ided. Seal rating is base d smooth. S/SPECIFICATION 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) (30 1.2~1.8N-m (0.5 ~ 4.0 sq 10 ~ 11 mm COM COR	ed on NS IP65 04 or 316SS for 4 (0.9~1.3 Lb-Ft) mm / 20-12AWG PORATION JSB; 3A; 32	N A REV B

