



For power connector, crimp terminals are supplied for hot and neutral connection. Ground wire supplied with an M3 ring terminal applied to end of 6" ground lead.

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT. 6 JACK	CAT. 6 JACK

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

PIC RATINGS	
VOLTS:	125V
AMPS:	15A
SCCR:	10kA

OPERATING TEMPERATURE:				(-10°C / +60° C (+14° F / +140° F))				
UNLESS OTHERWISE SPECIFIED:		DRAWN BY	ADM	MENCOM CORPORATION				
DIMENSIONS ARE IN INCHES AND [MM]		DRAWN DATE	08/18/2021					
		CHECKED BY	APR					
		CHECK DATE	08/18/2021					
				TITLE: SIMPLX, RJ45, SZ16 PL ONLY				
MATERIAL		COMMENTS:		SIZE	DWG. NO.			REV
FINISH				B	DP1-RJ45-PL16			B
DO NOT SCALE DRAWING				SCALE: 1:1	WEIGHT:		SHEET 1 OF 1	