



TS SYSTEM ALLOWS UNIT TO BE SNAP FASTENED ONTO DIN EN 50022 RAIL.

OR

MOUNTING HOLES IN BOTTOM OF UNIT ALLOW FOR MOUNTING INSIDE OF PANELS WITH FIXED FASTENERS

For power connector, crimp terminals are supplied for hot and neutral connection. Ground wire supplied with an M3 ring terminal applied to end of 6" ground lead.

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

MATERIALS	
BODY:	POLYAMIDE
PLATE:	STAINLESS STEEL

		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	DCG
			DRAWN DATE	07/03/2019
			CHECKED BY	DCG
			CHECK DATE	07/03/2019
		MATERIAL	COMMENTS:	
		FINISH		
		DO NOT SCALE DRAWING		

PIC RATINGS/SPECIFICATIONS	
VOLTS:	125V
AMPS:	15A
SCCR:	10kA
INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
WIRE STRIP LENGTH:	10 ~ 11 mm

MENCOM CORPORATION		
TITLE: SMPLX; RJ; DINRAIL 16		
SIZE B	DWG. NO. DP1-RJ45-TS	REV B
SCALE: 1:1	WEIGHT:	SHEET 1 OF 1