



STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT. 6 JACK	CAT. 6 JACK

MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

HOUSING MATERIALS	
BODY:	EPOXY COATED DIE CAST ALUMINUM
GASKET:	THERMOPLASTIC ELASTOMER
HANDLE:	POLYAMIDE
LEVERS:	STAINLESS STEEL



UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES AND [MM]	
MATERIAL	
FINISH	
DO NOT SCALE DRAWING	

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS							
VOLTS:		250V					
AMPS:		3A					
SCCR:		0.2kA					
NEMA/UL EN 60529:		4, 4X, 12 IP65					
MOUNTING SCREW SIZE:		M4 (8-32) (304 or 316SS for 4X)					
MOUNTING SCREW TORQUE:		1.2~1.8N-m (0.9~1.3 Lb-Ft)					
INCOMING POWER WIRE SIZE:		0.5 ~ 4.0 sq mm / 20-12AWG					
WIRE STRIP LENGTH:		10 ~ 11 mm					
DRAWN BY	DCG	MENCOM CORPORATION TITLE: DPLX 250V; RJ45; 3A; 32					
DRAWN DATE	05/15/2019						
CHECKED BY	GO						
CHECK DATE	05/15/2019						
COMMENTS:		SIZE		DWG. NO.		REV	
		B		DP220-RJ45-R-32		C	
		SCALE: 2:3		WEIGHT:		SHEET 1 OF 1	