



EUROPEAN RCBO CIRCUIT BREAKER, (RCD / GFCI WITH OVER CURRENT CIRCUIT PROTECTION), 16 AMPERE-230 VOLT, SINGLE POLE + NEUTRAL, 50/60 HZ, 30 Ma TRIP, 45mmX45mm MODULAR SIZE, TEST/BUTTON, INDICATOR LIGHT.

EUROPEAN "SCHUKO" 16 AMPERE-250 VOLT MODULAR OUTLET CEE7 TYPE F (EU1-16R), SHUTTERED CONTACTS, 2 POLE-3 WIRE GROUNDING (2P+E)

PANEL CUTOUT

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS	
VOLTS:	250V
AMPS:	3A
NEMA/UL EN 60529:	4, 12 IP65
PANEL THICKNESS:	5.0mm max
MOUNTING SCREW TORQUE:	0.8N-m
TERMINAL BLOCK TORQUE:	0.5N-m
INCOMING POWER WIRE SIZE:	0.25 - 2.5 sq mm / 24-12AWG
WIRE STRIP LENGTH:	7 - 8 mm

HOUSING MATERIALS	
BODY:	NICKEL PLATED ZINC
GASKETS:	PUR FIPG
FRONT COVER:	POLYCARBONATE
LATCH & LOCK:	PBT

MOUNTING KIT ORDERED SEPARATELY CONTAINS M4X0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES AND [MM]	
MATERIAL	
FINISH	
DO NOT SCALE DRAWING	

DRAWN BY	dcg
DRAWN DATE	01/15/2019
CHECKED BY	DCG
CHECK DATE	01/15/2019

MENCOM CORPORATION		
TITLE:		
SCHUKO W/GFI BRKR; RJ45; 3A;48		

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT. 6 JACK	CAT. 6 JACK

SIZE	DWG. NO.	REV
B	EPGF-RJ45-R-48	C
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1