



These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS			
BODY: GASKET: HANDLE: LEVERS:	EPOXY COATED DIE CAST ALUMINUM	VOLTS:	125V		
		AMPS:	10A		
		SCCR:	0.2kA		
		NEMA/UL   EN 60529:	4, 4X, 12   IP65		
		MOUNTING SCREW SIZE:	M5 (10-32) (304 or 316SS for 4X)		
		MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)		
		INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG		
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]		DRAWN BY	DCG		
		DRAWN DATE	11/21/2018		
		CHECKED BY	GO		
		CHECK DATE	11/26/2018		
		COMMENTS:			
		MATERIAL			
		FINISH			
		DO NOT SCALE DRAWING			
MENCOM CORPORATION TITLE: GFI; 10A; 32 SURF MNT		SIZE	DWG. NO.		REV
		B	GF-10R-P32		B
		SCALE: 2:3	WEIGHT:		SHEET 1 OF 1

MOUNTING KIT ORDERED SEPARATELY CONTAINS M5x0.8 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M5 NUT  
P/N: D-PIC-MT-M5



PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.