		[126] 5.0	-			<b>→</b> <sup>[4]</sup>	
			[92] 3.6		R		
	[8	CUTOUT <sup>38]</sup>	[ <b>4.5</b> ] - ∅.18			These devices shall be mounted on enclosu thickness and with adequate spacing provid mounting to a surface that is clean, flat and	led. Seal rating is based on
	J.2	40	4X			PIC RATINGS	S/SPECIFICATIONS
	$\bigcirc$					VOLTS:	125V
	$\bigcirc$				HOUSING MATERIALS		5A
						AMPS: SCCR	
		[65	5]	BODY:	EPOXY COATED DIE CAST ALUMINUM	SCCR: NEMA/UL   EN 60529:	0.2kA 4, 4X, 12   IP65
	O [76] 2.99	[65 2.5		BODY: GASKET:	EPOXY COATED DIE CAST ALUMINUM THERMOPLASTIC ELASTOMER	SCCR: NEMA/UL   EN 60529: R MOUNTING SCREW SIZE:	0.2kA 4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X)
	[76]			BODY:	EPOXY COATED DIE CAST ALUMINUM	SCCR: NEMA/UL   EN 60529:	0.2kA 4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X) 1.2~1.8N-m (0.9~1.3 Lb-Ft)
	[76]		56	BODY: GASKET: HANDLE: LEVERS:	EPOXY COATED DIE CAST ALUMINUM THERMOPLASTIC ELASTOMER POLYAMIDE STAINLESS STEEL C / +60° C (-4° F / +140° F ))	SCCR: NEMA/UL   EN 60529: MOUNTING SCREW SIZE: MOUNTING SCREW TORQUE: INCOMING POWER WIRE SIZE: WIRE STRIP LENGTH:	0.2kA 4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X) 1.2~1.8N-m (0.9~1.3 Lb-Ft)
	[76]			BODY: GASKET: HANDLE: LEVERS: G TEMPERATURE: (-20°	EPOXY COATED DIE CAST ALUMINUM THERMOPLASTIC ELASTOMER POLYAMIDE STAINLESS STEEL C / +60° C (-4° F / +140° F )) UNLESS OTHERWISE SPECIFIE	SCCR: NEMA/UL   EN 60529: MOUNTING SCREW SIZE: MOUNTING SCREW TORQUE: INCOMING POWER WIRE SIZE: WIRE STRIP LENGTH: DCG MENC	0.2kA 4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X) 1.2~1.8N-m (0.9~1.3 Lb-Ft) 0.5 ~ 4.0 sq mm / 20-12AWG
	[76]		Derating Mounting B Separately	BODY: GASKET: HANDLE: LEVERS: S TEMPERATURE: (-20° KIT ORDERED CONTAINS	EPOXY COATED DIE CAST ALUMINUM THERMOPLASTIC ELASTOMER POLYAMIDE STAINLESS STEEL C / +60° C (-4° F / +140° F ))	SCCR: NEMA/UL   EN 60529: R MOUNTING SCREW SIZE: MOUNTING SCREW TORQUE: INCOMING POWER WIRE SIZE: WIRE STRIP LENGTH: ED: DRAWN BY DCG MENC	0.2kA 4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X) 1.2~1.8N-m (0.9~1.3 Lb-Ft) 0.5 ~ 4.0 sq mm / 20-12AWG 10 ~ 11 mm
			Derating MOUNTING I SEPARATELY M4x0.7 SS SC	BODY: GASKET: HANDLE: LEVERS: TEMPERATURE: (-20° KIT ORDERED CONTAINS CONTAINS CREW, NYLON WASHER, VASHER AND M4 NUT	EPOXY COATED DIE CAST ALUMINUM THERMOPLASTIC ELASTOMER POLYAMIDE STAINLESS STEEL C / +60° C (-4° F / +140° F )) UNLESS OTHERWISE SPECIFIE	SCCR: NEMA/UL   EN 60529: R MOUNTING SCREW SIZE: MOUNTING SCREW TORQUE: INCOMING POWER WIRE SIZE: WIRE STRIP LENGTH: DRAWN BY DCG MENC DRAWN DATE 08/16/2021 CHECKED BY DCG TITLE:	0.2kA 4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X) 1.2~1.8N-m (0.9~1.3 Lb-Ft) 0.5 ~ 4.0 sq mm / 20-12AWG 10 ~ 11 mm
		2.5 	DPERATING MOUNTING H SEPARATELY M4x0.7 SS SC SPLIT LOCKW P/N: D-PIC- PROPRIETARY AND CON	BODY: GASKET: HANDLE: LEVERS: TEMPERATURE: (-20° CONTAINS CONTAINS CREW, NYLON WASHER, ASHER AND M4 NUT MT ONFIDENTIAL TAINED IN THIS	EPOXY COATED DIE CAST ALUMINUM THERMOPLASTIC ELASTOMER POLYAMIDE STAINLESS STEEL COV +60° C (-4° F / +140° F )) UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES AND [MM]	SCCR: NEMA/UL   EN 60529: MOUNTING SCREW SIZE: MOUNTING SCREW TORQUE: INCOMING POWER WIRE SIZE: WIRE STRIP LENGTH: DRAWN BY DCG DRAWN DATE 08/16/2021 CHECK DATE 08/16/2021 CHECK DATE 08/16/2021 COMMENTS:	0.2kA 4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X) 1.2~1.8N-m (0.9~1.3 Lb-Ft) 0.5 ~ 4.0 sq mm / 20-12AWG 10 ~ 11 mm OM CORPORATION GF; DB25; 5A; 32
	[76] 2.99 [11 4.3 CONFIGURATIONS UNLESS OTHE	2.5 10] 33 ERWISE NOTED	Derating MOUNTING I SEPARATELY M4x0.7 SS SC SPLIT LOCKW P/N: D-PIC- PROPRIETARY AND C DE INFORMATION CON DRAWING IS THE SOLE PI MENCOM CORPORATIO	BODY: GASKET: HANDLE: LEVERS: TEMPERATURE: (-20° KIT ORDERED CONTAINS CREW, NYLON WASHER, VASHER AND M4 NUT MT ONFIDENTIAL GONFIDENTIAL ROPERTY OF N, ANY	EPOXY COATED DIE CAST ALUMINUM THERMOPLASTIC ELASTOMER POLYAMIDE STAINLESS STEEL C / +60° C (-4° F / +140° F )) UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES AND [MM] MATERIAL	SCCR: NEMA/UL   EN 60529: MOUNTING SCREW SIZE: MOUNTING SCREW TORQUE: INCOMING POWER WIRE SIZE: WIRE STRIP LENGTH: DRAWN BY DCG DRAWN DATE 08/16/2021 CHECK DATE 08/16/2021 CHECK DATE 08/16/2021 CHECK DATE 08/16/2021 CHECK DATE 08/16/2021 CHECK DATE 08/16/2021 CHECK DATE 08/16/2021	0.2kA 4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X) 1.2~1.8N-m (0.9~1.3 Lb-Ft) 0.5 ~ 4.0 sq mm / 20-12AWG 10 ~ 11 mm OM CORPORATION GF; DB25; 5A; 32 NO. REV
STANDARD C CONN. TYPE D-SUB	[76] 2.99 [11 4.3 CONFIGURATIONS UNLESS OTHE EXTERIOR INT	2.5 	56 OPERATING MOUNTING H SEPARATELY M4x0.7 SS SC SPLIT LOCKW P/N: D-PIC- PROPRIETARY AND CON DRAWING IS THE SOLE PI	BODY: GASKET: HANDLE: LEVERS: TEMPERATURE: (-20° KIT ORDERED CONTAINS CREW, NYLON WASHER, VASHER AND M4 NUT MT ONFIDENTIAL INNED IN THIS ROPERTY OF N. ANY OR AS A WHOLE KIMISSION OF	EPOXY COATED DIE CAST ALUMINUM THERMOPLASTIC ELASTOMER POLYAMIDE STAINLESS STEEL CC / +60° C (-4° F / +140° F )) UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES AND [MM]	SCCR: NEMA/UL   EN 60529: MOUNTING SCREW SIZE: MOUNTING SCREW TORQUE: INCOMING POWER WIRE SIZE: WIRE STRIP LENGTH: DRAWN DATE 08/16/2021 CHECK DATE 08/16/2021	0.2kA 4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X) 1.2~1.8N-m (0.9~1.3 Lb-Ft) 0.5 ~ 4.0 sq mm / 20-12AWG 10 ~ 11 mm OM CORPORATION GF; DB25; 5A; 32