



STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT. 6 JACK	CAT. 6 JACK
ALL D-SUBS	FEMALE	MALE

MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

HOUSING MATERIALS	
BODY:	EPOXY COATED DIE CAST ALUMINUM
GASKET:	THERMOPLASTIC ELASTOMER
HANDLE:	POLYAMIDE
LEVERS:	STAINLESS STEEL



UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES AND [MM]	
MATERIAL	
FINISH	
DO NOT SCALE DRAWING	

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS			
VOLTS:		125V	
AMPS:		15A	
SCCR:		0.2kA	
NEMA/UL EN 60529:		4, 12 IP65	
PANEL THICKNESS:		5.0mm max	
MOUNTING SCREW TORQUE:		0.8N-m	
TERMINAL BLOCK TORQUE:		0.5N-m	
INCOMING POWER WIRE SIZE:		0.25 - 2.5 sq mm / 24-12AWG	
WIRE STRIP LENGTH:		7 - 8 mm	
DRAWN BY		DCG	
DRAWN DATE		11/21/2018	
CHECKED BY		GO	
CHECK DATE		11/26/2018	
COMMENTS:			
MENCOM CORPORATION			
TITLE:			
GF; DDB9; RJ45; 15A; 32			
SIZE	DWG. NO.		REV
B	GF-DB9-RJ45-15R-32		D
SCALE: 2:3		WEIGHT:	SHEET 1 OF 1