


80DB9FF
9 PIN D-SUB CONFIGURED
FEMALE EXTERIOR/ FEMALE INTERIOR



A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS	
VOLTS:	125V
AMPS:	15A
SCCR:	10kA
NEMA/UL EN 60529:	4, 12 IP65
PANEL THICKNESS:	5.0mm max
MOUNTING SCREW TORQUE:	0.8N-m
TERMINAL BLOCK TORQUE:	0.5N-m
INCOMING POWER WIRE SIZE:	0.25 - 2.5 sq mm / 24-12AWG
WIRE STRIP LENGTH:	7 - 8 mm

HOUSING MATERIALS		MENCOM CORPORATION	
BODY:	EPOXY COATED DIE CAST ALUMINUM	TITLE: GF; DB9 FF; RJ45; NR; 32	
GASKET:	THERMOPLASTIC ELASTOMER		
HANDLE:	POLYAMIDE		
LEVERS:	STAINLESS STEEL		
UNLESS OTHERWISE SPECIFIED:		DRAWN BY	DCG
DIMENSIONS ARE IN INCHES AND [MM]		DRAWN DATE	11/21/2018
		CHECKED BY	GO
		CHECK DATE	11/26/2018
		COMMENTS:	
MATERIAL		SIZE	DWG. NO.
FINISH		B	GF-DB9F-RJ45-NR-32
DO NOT SCALE DRAWING		SCALE: 2:3	WEIGHT:
		SHEET 1 OF 1	

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK