



STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK

	HOUSING MATERIALS
BODY:	EPOXY COATED DIE CAST ALUMINUM
GASKET:	THERMOPLASTIC ELASTOMER
HANDLE:	STAINLESS STEEL

OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° F))

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M6x1 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M6 NUT

P/N: D-PIC48-MT

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.



UNLESS OTHERWISE SPECIFIED:

S DIMENSIONS ARE IN INCHES
AND [MM]

	MATERIAL
--	----------

FINISH

DO NOT SCALE DRAWING

PIC RATINGS/SPECIFICATIONS	
VOLTS:	125V
AMPS:	3A
SCCR:	0.2kA
NEMA/UL EN 60529:	4, 4X, 12 IP65
MOUNTING SCREW SIZE:	M6 (1/4-20) (304 or 316SS for 4X)
MOUNTING SCREW TORQUE:	3.0~3.6N·m (2.2~2.7 Lb·Ft)
INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
WIRE STRIP LENGTH:	10 ~ 11 mm

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

DRAWN BY		ADM		MENCOM CORPORATION TITLE: GFI; RJ45; 2USB-AFAF; 3A; 48			
DRAWN DATE		08/27/2021					
CHECKED BY		DCG					
CHECK DATE		08/27/2021					
COMMENTS:							
		SIZE		DWG. NO.		REV	
		B		GF-RJ45-2USB-AFAF-R-48		B	
		SCALE: 1:2		WEIGHT:		SHEET 1 OF 1	