



PART NUMBER	LENGTH "L"
GF-RJ45-USB-03-R-32	3 FEET
GF-RJ45-USB-06-R-32	6 FEET
GF-RJ45-USB-10-R-32	10 FEET



These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS	
VOLTS:	125V
AMPS:	3A
SCCR:	0.2kA
NEMA/UL   EN 60529:	4, 4X, 12   IP65
MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
MOUNTING SCREW TORQUE:	1.2~1.8N·m (0.9~1.3 Lb·Ft)
INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
WIRE STRIP LENGTH:	10 ~ 11 mm

**UL**  
LISTED  
ENCL. ACC.  
5JR2

D:	DRAWN BY	DCG
	DRAWN DATE	11/26/2018
	CHECKED BY	GO
	CHECK DATE	11/26/2018

TITLE:

GFI; RJ45; USB-PCBL; 3A;

32

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT. 6 JACK	CAT. 6 JACK

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.

		MATERIAL
		FINISH
		DO NOT SCALE DRAWING

COMMENTS:

SIZE <b>B</b>	DWG. NO. GF-RJ45-USB-ZZ-R-32	REV <b>E</b>
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1