



MCG-21R
FOR [9-16] .354-.630"
CABLE DIA.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS	
BODY:	EPOXY COATED DIE CAST ALUMINUM	VOLTS:	125V
GASKET:	THERMOPLASTIC ELASTOMER	AMPS:	20A
HANDLE:	POLYAMIDE	SCCR:	0.2kA
LEVERS:	STAINLESS STEEL	NEMA/UL EN 60529:	4, 4X, 12 IP65
MOUNTING KIT ORDERED SEPARATELY CONTAINS M5X0.8 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M5 NUT		MOUNTING SCREW SIZE:	M5 (10-32) (304 or 316SS for 4X)
P/N: D-PIC-MT-M5		MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)
UNLESS OTHERWISE SPECIFIED:		INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
DIMENSIONS ARE IN INCHES AND [MM]		DRAWN BY	DCG
MATERIAL		DRAWN DATE	06/16/2022
FINISH		CHECKED BY	APR
DO NOT SCALE DRAWING		CHECK DATE	06/16/2022
COMMENTS:		MENCOM CORPORATION	
TITLE:		GF20; 20A; 32 SURF MNT	
SIZE		DWG. NO.	REV
B		GF20-20R-P32	A
SCALE: 2:3		WEIGHT:	SHEET 1 OF 1

MOUNTING KIT ORDERED SEPARATELY CONTAINS M5X0.8 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M5 NUT
P/N: D-PIC-MT-M5



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.