



MATERIALS	
BODY:	BLACK POLYAMIDE
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE SEAL:	NBR
INSERT:	YELLOW PVC
COUPLING:	NICKEL PLATED BRASS
RATINGS	
AMPS:	14AWG - 18A max 16AWG - 13A max 18AWG - 10A max 20-22AWG - 4A max
VOLTS:	600V MAX
SEAL:	IP67
CABLE RANGE:	14AWG - 22AWG 0.20" - 0.51" (5mm - 13mm) OD
APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED

CABLE ASSEMBLY SOCKET FOR CONTROL, SIGNAL, AND POWER  
DISTRIBUTION FOR USE IN HAZARDOUS LOCATIONS

Voltage rating is 600V or the  
rating of the cable, whichever  
is less.

Connections made via screw  
terminals.

UNLESS OTHERWISE SPECIFIED:	DRAWN BY	JJH	MENCOM CORPORATION
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	02/13/2024	
CHECKED BY	CHECK DATE	DWM 02/14/2024	
TITLE:			
SIZE	DWG. NO.	REV	
B	H2MIN-3FP-FW	A	
SCALE: 2:1	WEIGHT:		SHEET 1 OF 1
DO NOT SCALE DRAWING			

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.