



WARNING
 Risk of Electrical Shock
 De Niet Aansluiten
 Under Load
 Risque de chocs
 électriques
 Ne pas brancher
 sous tension

WARNING LABEL

CABLE ASSEMBLY PLUG FOR CONTROL, SIGNAL AND POWER DISTRIBUTION FOR USE IN HAZARDOUS LOCATIONS

Voltage rating is 600V or the rating of the cable, whichever is less.

Connections made via screw terminals.

MATERIALS	
BODY:	BLACK POLYAMIDE
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE SEAL:	NBR
INSERT:	YELLOW PVC
COUPLING:	NICKEL PLATED BRASS
RATINGS	
AMPS:	14AWG - 18A max 16AWG - 13A max 18AWG - 10A max 20-22AWG - 4A max
VOLTS:	600V MAX
SEAL:	IP67
CABLE RANGE:	14AWG - 22AWG 0.20" - 0.51" (5mm - 13mm) OD
APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	DRAWN BY	JJH
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	02/13/2024
	CHECKED BY	DWM
	CHECK DATE	02/14/2024
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION		
TITLE:		
SIZE	DWG. NO.	REV
B	H2MIN-3MPM-FW	A
SCALE: 2:1	WEIGHT:	SHEET 1 OF 1