



## CABLE ASSEMBLY PLUG FOR CONTROL, SIGNAL AND POWER DISTRIBUTION FOR USE IN HAZARDOUS LOCATIONS

MATERIALS	
BODY:	BLACK POLYAMIDE
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE SEAL:	NBR
INSERT:	YELLOW PVC
COUPLING:	NICKEL PLATED BRASS

  

RATINGS	
AMPS:	14AWG - 12A max
	16AWG - 8A max
	18AWG - 5.5A max
	20-22AWG - 4A max
VOLTS:	600V MAX
SEAL:	IP67
CABLE RANGE:	14AWG - 22AWG
	0.20" - 0.51" (5mm - 13mm) OD

  

APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED

Voltage rating is 600V or the rating of the cable, whichever is less.

Connections made via screw terminal

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	DRAWN BY	JJH	MENCOM CORPORATION
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	02/14/2024	
	CHECKED BY	JJH	
	CHECK DATE	02/14/2024	
COMMENTS:			
SIZE	DWG. NO.	REV	
B	H2MIN-5MPM-FW	A	
SCALE: 2:1	WEIGHT:		SHEET 1 OF 1