



MCV

FUNCTION

FUNCTION

19	ALL PORTS PIN 1	V+
6	ALL PORTS PIN 3	V-
12	ALL PORTS PIN 5	GROUND
7	PORT 1 PIN 2	I/O
15	PORT 1 PIN 4	I/O
4	PORT 2 PIN 2	I/O
5	PORT 2 PIN 4	I/O
8	PORT 3 PIN 2	I/O
16	PORT 3 PIN 4	I/O
14	PORT 4 PIN 2	I/O
3	PORT 4 PIN 4	I/O

MATERIALS:

BODY:	PBT
MARKERS:	POLYAMIDE
SHELLS:	NICKEL PLATED BRASS
INSERTS:	POLYAMIDE
CONTACTS:	GOLD PLATED COPPER ALLOY
O-RINGS:	NBR

RATINGS:	
VOLTS:	48VDC MAX
AMPS:	3A PER PORT, 8A PER BLOCK

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

DRAWN BY	JJH
DRAWN DATE	03/13/2020
CHECKED BY	ADM
CHECK DATE	03/13/2020

COMMENTS:

MATERIALS

FINISH

DO NOT SCALE DRAWING

MENCOM CORPORATION

TITLE:

SIZE

DWG. NO.

B JDC-45N-219-V000

REV

SCALE: 1:1

WEIGHT:

SHEET 1 OF 1