



PART NUMBER	LENGTH "L"
LP2-DP-USB-03.SLDDRW	3 FEET
LP2-DP-USB-06.SLDDRW	6 FEET
LP2-DP-USB-10.SLDDRW	10 FEET

(X4) USE PH2 SCREW DRIVER ON MOUNTING SCREWS. (REF. MOUNTING SCREW TORQUE)

ROTATE TWO TURNS COUNTER CLOCKWISE TO RELEASE THE TURN BUCKLE PRIOR TO TIGHTENING

TURN BUCKLES ROTATE 90 DEG. INTO THEIR CLAMPING POSITION AS MOUNTING SCREWS TIGHTEN. DO NOT OVER-TORQUE!

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

LOCK

DETAIL A
SCALE 1 : 1

SLIDE LATCH TO OPEN/CLOSE
ROTATE LOCK TO LOCK CLOSED

PIC RATINGS/SPECIFICATIONS	
VOLTS:	125V
AMPS:	15A
SCCR:	10kA
NEMA/UL EN 60529:	4, 12 IP65
PANEL THICKNESS:	5.0mm max
MOUNTING SCREW TORQUE:	0.8N-m
TERMINAL BLOCK TORQUE:	0.5N-m
INCOMING POWER WIRE SIZE:	0.25 - 2.5 sq mm / 24-12AWG
WIRE STRIP LENGTH:	7 - 8 mm

OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° F))		UNLESS OTHERWISE SPECIFIED:		
HOUSING MATERIALS		DRAWN BY: DG		
BODY:	NICKEL PLATED ZINC	DRAWN DATE:	06/26/2024	
GASKETS:	PUR FIPG	CHECKED BY:	RP	
FRONT COVER:	POLYCARBONATE	CHECK DATE:	06/26/2024	
LATCH & LOCK:	PBT	COMMENTS:		
BACK COVER:	POLYPROPYLENE			
MATERIAL		MENCORPORATION		
FINISH				
DO NOT SCALE DRAWING		TITLE: DPLX; USB-PCBL; LP2		
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCORPORATION IS PROHIBITED.		SIZE: B	DWG. NO.: LP2-DP-USB-ZZ	REV: B
		SCALE: 1:2	WEIGHT:	SHEET 1 OF 1