



NOTE; DUE TO THE TIGHT FIT BETWEEN THE BACK COVERS, A DB09-MF-* CABLE IS PRE-INSTALLED ON THE INTERIOR OF THIS CONNECTOR.

PART NUMBER	LENGTH "L"
LP3-2GF-DB9-03-RJ45-USB-AFAF	3 FEET
LP3-2GF-DB9-06-RJ45-USB-AFAF	6 FEET
LP3-2GF-DB9-10-RJ45-USB-AFAF	10 FEET

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS	
VOLTS:	125V
AMPS:	15A
SCCR:	10kA
NEMA/UL EN 60529:	4, 12 IP65
PANEL THICKNESS:	5.0mm max
MOUNTING SCREW TORQUE:	0.8N-m
TERMINAL BLOCK TORQUE:	0.5N-m
INCOMING POWER WIRE SIZE:	0.25 - 2.5 sq mm / 24-12AWG
WIRE STRIP LENGTH:	7 - 8 mm

OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° F))	
HOUSING MATERIALS	
BODY:	NICKEL PLATED ZINC
GASKETS:	PUR FIPG
FRONT COVER:	POLYCARBONATE
LATCH & LOCK:	PBT
BACK COVER:	POLYPROPYLENE
PLATE:	304 STAINLESS
UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES AND [MM]	
MATERIAL	
FINISH	
DO NOT SCALE DRAWING	

DRAWN BY	DCG	MENCOM CORPORATION			
DRAWN DATE	08/17/2018				
CHECKED BY	JJH				
CHECK DATE	08/17/2018				
		TITLE:			
		CC; 2GF; DB9-ZZ; RJ45; USB-AA; LP3			
COMMENTS:		SIZE		DWG. NO.	REV
		B		LP3-2GF-DB9-ZZ-RJ45-USB-AFAF	B
		SCALE: 1:2		WEIGHT:	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.