



PANEL CUTOUT

$[117.0^{+0.4}_{0.0}]$   
 $4.61^{+0.02}_{-0.00}$

$[2.0 \text{ MAX}]$   
 $R0.08 \text{ MAX}$

$[130.2]$   
 $5.13$

$[91.0^{+0.4}_{0.0}]$   
 $3.58^{+0.02}_{-0.00}$

$[123.6]$   
 $4.87$

$[79.7]$   
 $3.14$

3 POLE PLUGGABLE  
TERMINAL BLOCK  
FOR INCOMING POWER

$[116.9]$   
 $4.60$

$[25.1]$   
 $0.99$

(X4) USE PH2 SCREW  
DRIVER ON MOUNTING  
SCREWS. (REF. MOUNTING  
SCREW TORQUE)

ROTATE TWO TURNS COUNTER  
CLOCKWISE TO RELEASE THE  
TURN BUCKLE PRIOR TO TIGHTENING

TURN BUCKLES ROTATE 90 DEG. INTO  
THEIR CLAMPING POSITION AS  
MOUNTING SCREWS TIGHTEN.  
DO NOT OVER-TORQUE!

These devices shall be mounted on enclosures having adequate strength and  
thickness and with adequate spacing provided. Seal rating is based on  
mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS

VOLTS:	125V
AMPS:	3A
SCCR:	0.2kA
NEMA/UL   EN 60529:	4, 12   IP65
PANEL THICKNESS:	5.0mm max
MOUNTING SCREW TORQUE:	0.8N-m
TERMINAL BLOCK TORQUE:	0.5N-m
INCOMING POWER WIRE SIZE:	0.25 - 2.5 sq mm / 24-12AWG
WIRE STRIP LENGTH:	7 - 8 mm



OPERATING TEMPERATURE: ( -20°C / +60° C ( -4° F / +140° F ) )		
HOUSING MATERIALS		UNLESS OTHERWISE SPECIFIED:  DIMENSIONS ARE IN INCHES AND [MM]
BODY:	NICKEL PLATED ZINC	
GASKETS:	PUR FIPG	
FRONT COVER:	POLYCARBONATE	
LATCH & LOCK:	PBT	
BACK COVER:	POLYPROPYLENE	

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.

MATERIAL

FINISH

DO NOT SCALE DRAWING

DRAWN BY	DG
DRAWN DATE	03/09/2018
CHECKED BY	
CHECK DATE	

COMMENTS:

MENCOM CORPORATION

TITLE:

DPLX; 3A; LP3

SIZE	DWG. NO.	REV
<b>B</b>	LP3-DP-R	<b>A</b>
SCALE: 1:2	WEIGHT:	SHEET 1 OF 1