





VOLTS

AMPS

TEMP:

PROPRIETARY AND CONFIDENTIAL

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

5

3

P/N	L	STD?
MAC-3MFP-0.5M	20" [0.5M]	NO
MAC-3MFP-1M	40" [1M]	YES
MAC-3MFP-2M	79" [2M]	YES
MAC-3MFP-3M	118" [3M]	NO
MAC-3MFP-4M	157" [4M]	NO
MAC-3MFP-5M	197" [5M]	YES
MAC-3MFP-6M	236" [6M]	NO
MAC-3MFP-8M	315" [8M]	NO
MAC-3MFP-10M	393" [10M]	YES
MAC-3MFP-15M	590" [15M]	YES
MAC-3MFP-20M	786" [20M]	NO
MAC-3MFP-25M	983" [25M]	NO
MAC-3MFP-30M	1179" [30M]	NO

					• [•	· · · · · · · · · · · · · · · · · · ·	
					ED AS NOT BEING STA EQUIRE MINIMUM ORI		
	UNLESS OTHERWISE SPECIFIED:	DRAWN BY	ADM	A A E N L			
	DIMENSIONS ARE IN INCHES	DRAWN DATE	07/31/2023	MEIN	COM CORPC	RATION	
	AND [MM]	CHECKED BY	JJH	TITLE:			
		CHECK DATE	08/01/2023				/
300V		COMMENTS	: :	_			
4A	MATERIAL			SIZE DWG.	NO.	REV	
105°C	FINISH			В	MAC-3MFP-Z	Z C	
	DO NOT SCALE DRAWING			SCALE: 1.5:1	WEIGHT:	SHEET 1 OF 1	
	2			2		1	

TABLE A

3	MATERIALS	
	BODY:	YELLOW PVC
	CONTACTS:	GOLD PLATED COPPER ALLOY
	CABLE:	
	STYLE:	AWM
	AWG:	22 AWG
	JACKET:	YELLOW PVC
	VOLTAGE:	600V
	SHIELD:	NO
	COUPLING:	NICKEL PLATED BRASS
	INSERT:	POLYAMIDE
	O-RING:	FPM
	APPROVALS	
4	US:	UL LISTED
	CANADA:	C-UL LISTED
	ROHS:	YES
	CE & UKCA:	YES
	RATINGS	
	PROTECTION CLASS:	UL TYPE 4 & 12, IEC IP69