



B	MATERIALS:	
	BODY:	POLYAMIDE
	COUPLING:	NICKEL PLATED BRASS
	CONTACTS:	GOLD PLATED COPPER ALLOY
	GROMMET:	NBR
	O-RING:	NBR
	SPECIFICATIONS:	
	WIRE RANGE:	18-24AWG [1.0 - 0.25sqmm]
	CABLE RANGE:	0.118 - 0.255 [3 - 6.5mm]
A	CONNECTION:	SCREW TERMINALS
	VOLTS:	250V
	AMPS:	4A
	SEAL:	IP67
	TEMP RANGE:	STATIC: -40°C - +105°C
		DYNAMIC: -20°C -+105°C

Voltage rating is 250V or the rating of the cable, whichever is less.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	ADM	MENCOM CORPORATION		
	DRAWN DATE	07/25/2023			
	CHECKED BY	JJH	TITLE: 3 PL ML MAC FW PLUG		
	CHECK DATE	07/25/2023			
	COMMENTS:		SIZE	DWG. NO.	REV
MATERIAL			B	MAC-3MP-FW07-R	B
FINISH			SCALE: 2:1	WEIGHT:	SHEET 1 OF 1
DO NOT SCALE DRAWING					