PIN #	COLOR
1	RED w/BLACK
2	RED w/WHITE
3	RED
4	GREEN / YELLOW





P/N	L
MAC-4FR-2	12" [0.3m]
MAC-4FR-2-0.5M	20" [0.5m]
MAC-4FR-2-0.6M	24" [0.6m]
MAC-4FR-2-1M	40" [1.0m]
MAC-4FR-2-2M	79" [2.0m]
MAC-4FR-2-3M	118" [3.0m]
MAC-4FR-2-4M	157" [4.0m]
MAC-4FR-2-5M	193" [5.0m]
MAC-4FR-2-6M	236" [6.0m]

OTHER LENGTHS ARE AVAILABLE
PLEASE CONSULT FACTORY

FOR LENGTHS OF 20" [0.5m] AND LONGER,
AN O-RING AND LOCKNUT ARE INCLUDED

MATERIALS	
SHELL:	CLEAR ANODIZED ALUMINUM
CONTACTS:	GOLD PLATED COPPER ALLOY
WIRES:	
STYLE:	UL 1007/1569
AWG:	22 AWG
JACKET:	PVC
VOLTAGE:	300V
INSERT:	POLYAMIDE
O-RING:	NBR
NUT:	ZINC PLATED STEEL
APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED
ROHS:	YES
CE & UKCA:	YES
RATINGS	
PROTECTION CLASS:	UL TYPE 4 & 12, IEC IP69

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS	300V
AMPS	4A
TEMP:	105°C

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES AND [MM]
MATERIAL
FINISH
DO NOT SCALE DRAWING

DRAWN BY	ADM
DRAWN DATE	08/02/2023
CHECKED BY	JJH
CHECK DATE	08/03/2023

COMMENTS:

MENCOM CORPORATION

TITLE:

SIZE B | DWG. NO. MAC-4FR-2-ZZ | REV B

SCALE: 2:1 | WEIGHT: | SHEET 1 OF 1