	8			6		5			3
PIN#	COLOR					V.			
1									
	RED w/BLACK								
2	RED w/WHITE								
3	RED								
4	GREEN / YELLOW								
-									
	-	L -							
		Р	PG 9—			-1/2-20 UNF	2A		
						., 0 0111	P		¥
		`							•
							/ //	40	[18]
									.71
					1 1 8 0 8 0 9 0 9 0 9				
•									
>									
			[6.2]			[13.8]			
						13.8] .54			
MATERIALS									
SHELL:	NICKEL PLATED BRA								
SHELL: CONTACTS:									
SHELL:	GOLD PLATED COP								
SHELL: CONTACTS:									
SHELL: CONTACTS: WIRES:	GOLD PLATED COP STYLE: UL 1007/1569								
SHELL: CONTACTS: WIRES:	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG								
SHELL: CONTACTS: WIRES:	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC								
SHELL: CONTACTS: WIRES: V(INSERT: O-RING:	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC DLTAGE: 300V POLYAMIDE NBR	PER ALLOY							
SHELL: CONTACTS: WIRES: VO INSERT:	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC DLTAGE: 300V POLYAMIDE	PER ALLOY							UNLESS OTHERWISE SPECIFIED
SHELL: CONTACTS: WIRES: V(INSERT: O-RING: NUT:	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC DLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRA	PER ALLOY							
SHELL: CONTACTS: WIRES: V(INSERT: O-RING: NUT: APPROVALS	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC DLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRA	PER ALLOY							UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
SHELL: CONTACTS: WIRES: VO INSERT: O-RING: NUT: APPROVALS US:	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC DLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRA	PER ALLOY							UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
SHELL: CONTACTS: WIRES: V(INSERT: O-RING: NUT: APPROVALS US: CANADA:	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC DLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRA UL LISTED C-UL LISTED	PER ALLOY				.54		2001/	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
SHELL: CONTACTS: WIRES: VO INSERT: O-RING: NUT: APPROVALS US:	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC DLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRA UL LISTED C-UL LISTED YES	PER ALLOY			PROP	.54	VOLTS	300V	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
SHELL: CONTACTS: WIRES: V(INSERT: O-RING: NUT: APPROVALS US: CANADA: ROHS:	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC DLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRA UL LISTED C-UL LISTED YES	PER ALLOY			PROP THE INFOI DRAWING MENCON	.54 PRIETARY AND CONFIDENTIAL RMATION CONTAINED IN THIS G IS THE SOLE PROPERTY OF M CORPORATION. ANY	AMPS	4A	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]
SHELL: CONTACTS: WIRES: VIRES: INSERT: O-RING: NUT: APPROVALS US: CANADA: ROHS: CE & UKCA: RATINGS	GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC DLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRA UL LISTED C-UL LISTED YES	NSS			PROP THE INFOI DRAWING MENCOD REPRODU WITHOUT	.54 PRIETARY AND CONFIDENTIAL IRMATION CONTAINED IN THIS G IS THE SOLE PROPERTY OF			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]

M	AC-4MR	-PG9-3M	118"	[3.0m]
M	AC-4MR	-PG9-4M	157"	[4.0m]
M	AC-4MR	-PG9-5M	193"	[5.0m]
M	AC-4MR	-PG9-6M	236"	[6.0m]
	-	r lengths ai Ase consul		
ADM	MEN	СОМ СО	RPORAT	ION
08/03/2023	TITI F:			
08/03/2023				A
	SIZE DWG.	NO.		REV
	B N	1AC-4MR-	PG9-ZZ	B
	SCALE: 2:1	WEIGHT:	SHI	ET 1 OF 1
	2		1	

С

В

L

12" [0.3m]

20" [0.5m]

24" [0.6m]

40" [1.0m]

79" [2.0m]

D

1

2

P/N

MAC-4MR-PG9

MAC-4MR-PG9-0.5M

MAC-4MR-PG9-0.6M

MAC-4MR-PG9-1M

MAC-4MR-PG9-2M