		/	6			3		2	·
PIN #	# COLOR								
1	RED w/WHITE								
2	RED								
3	GREEN / YELLOW								
4	RED w/YELLOW								
5	RED w/BLACK								
		1/2-14 NPT-			[25] 1.0		THREAD	P/N MAC-5FR-2	L 12" [0.2m]
								MAC-5FR-2-0.5M	1 20" [0.5m]
		Г							1 20" [0.5m] 1 24" [0.6m]
		[11.4		[14.3]				MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M	1 20" [0.5m] 1 24" [0.6m] 40" [1.0m]
	IALS CLEAR ANODIZED A	45		[14.3] .56				MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M	 A 20" [0.5m] A 24" [0.6m] 40" [1.0m] 79" [2.0m]
SHELL: CONTAC	CLEAR ANODIZED A	45	4]	[14.3] .56				MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M	 A 20" [0.5m] A 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m]
SHELL: CONTAC	CLEAR ANODIZED A	45		.56	' [0.5m] AND LON	GER,		MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-4M	 A 20" [0.5m] A 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m]
SHELL: CONTAC	CLEAR ANODIZED A CCTS: GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG	45	F	TOR LENGTHS OF 20'				MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-4M MAC-5FR-2-5M	 20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m]
SHELL: CONTAC	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC	45	F	.56 Or lengths of 20'				MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-4M	
MATERIA SHELL: CONTAC WIRES: INSERT:	CLEAR ANODIZED A CCTS: GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG	45	F	.56 Or lengths of 20'				MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-3M MAC-5FR-2-5M MAC-5FR-2-6M OTHER LENGTHS	 20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m] 236" [6.0m] S AVAILABLE,
SHELL: CONTAC WIRES: NSERT: D-RING:	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC VOLTAGE: 300V POLYAMIDE 5: NBR & FPM	45	F	.56 Or lengths of 20'		DED		MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-4M MAC-5FR-2-5M MAC-5FR-2-6M	 20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m] 236" [6.0m] S AVAILABLE,
SHELL: CONTAC WIRES: NSERT: D-RING:	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC VOLTAGE: 300V POLYAMIDE	45	F	.56 Or lengths of 20'		DED UNLESS OTHERWISE SPECIFIED		MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-3M MAC-5FR-2-5M MAC-5FR-2-6M OTHER LENGTHS	20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m] 236" [6.0m] S AVAILABLE, JLT FACTORY
SHELL: CONTAC WIRES: NIRES: NSERT: D-RING: NUT:	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC VOLTAGE: 300V POLYAMIDE S: NBR & FPM ZINC PLATED STEEL	45	F	.56 Or lengths of 20'		DED	DRAWN DATE 08/03/2023	MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-3M MAC-5FR-2-5M MAC-5FR-2-5M MAC-5FR-2-6M	20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m] 236" [6.0m] S AVAILABLE, JLT FACTORY
SHELL: CONTAC WIRES: INSERT: O-RING: NUT: APPROV	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC VOLTAGE: 300V POLYAMIDE S: NBR & FPM ZINC PLATED STEEL	45	F	.56 Or lengths of 20'		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-3M MAC-5FR-2-4M MAC-5FR-2-5M MAC-5FR-2-6M OTHER LENGTHS PLEASE CONSU	20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m] 236" [6.0m] S AVAILABLE, JLT FACTORY
SHELL: CONTAC WIRES: INSERT: O-RING: NUT: APPROV US:	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC VOLTAGE: 300V POLYAMIDE C: NBR & FPM ZINC PLATED STEEL	45	F	.56 Or lengths of 20'		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN DATE 08/03/2023 CHECKED BY JJH	MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-3M MAC-5FR-2-4M MAC-5FR-2-5M MAC-5FR-2-6M OTHER LENGTHS PLEASE CONSU	20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m] 236" [6.0m] S AVAILABLE, JLT FACTORY
SHELL: CONTAC WIRES: INSERT: O-RING: NUT: APPROV US: CANAD/	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC VOLTAGE: 300V POLYAMIDE C: NBR & FPM ZINC PLATED STEEL	45	F	.56 OR LENGTHS OF 20' AN O-RING AND LO	CKNUT ARE INCLU	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN DATE 08/03/2023 CHECKED BY JJH CHECK DATE 08/03/2023	MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-3M MAC-5FR-2-4M MAC-5FR-2-5M MAC-5FR-2-6M OTHER LENGTHS PLEASE CONSU	20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m] 236" [6.0m] S AVAILABLE, JULT FACTORY
SHELL: CONTAC WIRES: INSERT: O-RING: NUT: APPROV US: CANAD/ ROHS:	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC VOLTAGE: 300V POLYAMIDE S: NBR & FPM ZINC PLATED STEEL VALS UL LISTED DA: C-UL LISTED YES	45	F	OR LENGTHS OF 20' AN O-RING AND LO	VOLTS 300V	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN DATE 08/03/2023 CHECKED BY JJH	MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-3M MAC-5FR-2-5M MAC-5FR-2-5M MAC-5FR-2-6M	 20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m] 236" [6.0m] S AVAILABLE, FACTORY RPORATION
SHELL: CONTAC WIRES: INSERT: O-RING: NUT: APPROV US: CANAD/ ROHS:	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC VOLTAGE: 300V POLYAMIDE S: NBR & FPM ZINC PLATED STEEL VALS UL LISTED DA: C-UL LISTED YES	45	F	FOR LENGTHS OF 20' AN O-RING AND LO PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	VOLTS 300V AMPS 4A	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 08/03/2023 CHECKED BY JJH CHECK DATE 08/03/2023	MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-4M MAC-5FR-2-5M MAC-5FR-2-6M OTHER LENGTHS PLEASE CONSUL MENCOM COF TITLE:	20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 193" [5.0m] 236" [6.0m] S AVAILABLE, JLT FACTORY RPORATION
SHELL: CONTAC WIRES:	CLEAR ANODIZED A GOLD PLATED COP STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC VOLTAGE: 300V POLYAMIDE S: NBR & FPM ZINC PLATED STEEL VALS UL LISTED DA: C-UL LISTED YES KCA: YES	45	F	TOR LENGTHS OF 20' AN O-RING AND LO PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	VOLTS 300V	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 08/03/2023 CHECKED BY JJH CHECK DATE 08/03/2023	MAC-5FR-2-0.5M MAC-5FR-2-0.6M MAC-5FR-2-1M MAC-5FR-2-2M MAC-5FR-2-3M MAC-5FR-2-3M MAC-5FR-2-5M MAC-5FR-2-5M MAC-5FR-2-6M	20" [0.5m] 24" [0.6m] 40" [1.0m] 79" [2.0m] 118" [3.0m] 157" [4.0m] 236" [6.0m] S AVAILABLE, JLT FACTORY RPORATION