<b>DIN!</b> //									
PIN#	COLOR								
1	RED w/WHITE								
	RED								
	GREEN / YELLOW								
4	RED w/YELLOW								
5	<b>RED w/BLACK</b>								
6	RED w/BLUE								
		M20x1.5—						P/N	L
								P/N	L
				[25] //				MAC-4MR-M20	4011 [0.2.00]
									12" [0.3m]
				[25] 1.0				MAC-4MR-M20-0.	
				1.0 \				MAC-4MR-M20-0.	5M 20" [0.5m]
				1.0 N				MAC-4MR-M20-0. MAC-4MR-M20-0.	5M 20" [0.5m] 6M 24" [0.6m]
NATERIALS				1.0 \				MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1	5M 20" [0.5m] 6M 24" [0.6m] M 40" [1.0m]
	CLEAR ANODIZED ALL			1.0 				MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1M MAC-4MR-M20-2M	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   M 79" [2.0m]
SHELL: CONTACTS:	CLEAR ANODIZED ALL			1.0 				MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   M 79" [2.0m]
SHELL: CONTACTS:	CLEAR ANODIZED ALL GOLD PLATED COPPE	R ALLOY 7.6	14.9	1.0 				MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1M MAC-4MR-M20-2M	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   M 79" [2.0m]   M 118" [3.0m]
SHELL: CONTACTS:	CLEAR ANODIZED ALU : GOLD PLATED COPPEN STYLE: UL 1007/1569			1.0				MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1 MAC-4MR-M20-2 MAC-4MR-M20-3 MAC-4MR-M20-3	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   M 79" [2.0m]   M 118" [3.0m]   M 157" [4.0m]
SHELL: CONTACTS: WIRES:	CLEAR ANODIZED ALU : GOLD PLATED COPPEN STYLE: UL 1007/1569 AWG: 22 AWG	R ALLOY 7.6	14.9	1.0				MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1 MAC-4MR-M20-2 MAC-4MR-M20-3 MAC-4MR-M20-3 MAC-4MR-M20-4 MAC-4MR-M20-5	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   40" [2.0m]   40 1.0m]
	CLEAR ANODIZED ALU : GOLD PLATED COPPEN STYLE: UL 1007/1569	R ALLOY 7.6	14.9	1.0				MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1 MAC-4MR-M20-2 MAC-4MR-M20-3 MAC-4MR-M20-3	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   40" [2.0m]   40 1.0m]
SHELL: CONTACTS: WIRES:	CLEAR ANODIZED ALU : GOLD PLATED COPPER STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC	R ALLOY 7.6	14.9	1.0				MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1M MAC-4MR-M20-2M MAC-4MR-M20-3M MAC-4MR-M20-3M MAC-4MR-M20-5M MAC-4MR-M20-5M MAC-4MR-M20-6M	5M 20" [0.5m]   6M 24" [0.6m]   6M 40" [1.0m]   40 79" [2.0m]   40 118" [3.0m]   40 118" [3.0m]   40 118" [3.0m]   40 157" [4.0m]   40 193" [5.0m]   40 236" [6.0m]   41 4036
SHELL: CONTACTS: WIRES: V( NSERT:	CLEAR ANODIZED ALU : GOLD PLATED COPPEN STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC OLTAGE: 300V	R ALLOY 7.6	14.9	1.0				MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1 MAC-4MR-M20-2 MAC-4MR-M20-3 MAC-4MR-M20-4 MAC-4MR-M20-5 MAC-4MR-M20-5	5M 20" [0.5m]   6M 24" [0.6m]   6M 40" [1.0m]   40 79" [2.0m]   40 118" [3.0m]   40 118" [3.0m]   40 118" [3.0m]   40 157" [4.0m]   40 193" [5.0m]   40 236" [6.0m]   41 4036
SHELL: CONTACTS: WIRES: V( NSERT: D-RING:	CLEAR ANODIZED ALU : GOLD PLATED COPPEN STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC OLTAGE: 300V POLYAMIDE	R ALLOY [7.6	14.9	1.0		UNLESS OTHERWISE SPECIFIED		MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1M MAC-4MR-M20-2M MAC-4MR-M20-3M MAC-4MR-M20-3M MAC-4MR-M20-5M MAC-4MR-M20-5M MAC-4MR-M20-6M OTHER LENGTHS PLEASE CONS	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   40" [1.0m]   40" [2.0m]   40   118" [3.0m]   40   118" [3.0m]   40   118" [3.0m]   40   1236" [6.0m]   ARE AVAILABLE   ULT FACTORY
SHELL: CONTACTS: WIRES: V( NSERT: D-RING: NUT:	CLEAR ANODIZED ALU CLEAR ANODIZED ALU GOLD PLATED COPPER STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC OLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRASS	R ALLOY [7.6	14.9	1.0		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 08/	MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1 MAC-4MR-M20-2 MAC-4MR-M20-3 MAC-4MR-M20-3 MAC-4MR-M20-4 MAC-4MR-M20-5 MAC-4MR-M20-6 MAC-	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   40" [1.0m]   40" [2.0m]   40   118" [3.0m]   40   118" [3.0m]   40   118" [3.0m]   40   1236" [6.0m]   ARE AVAILABLE   ULT FACTORY
SHELL: CONTACTS: WIRES: V( NSERT: D-RING: IUT: APPROVALS	CLEAR ANODIZED ALU CLEAR ANODIZED ALU GOLD PLATED COPPER STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC OLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRASS	R ALLOY [7.6	14.9			DIMENSIONS ARE IN INCHES	DRAWN DATE 08/ CHECKED BY	MAC-4MR-M20-0.   MAC-4MR-M20-0.   MAC-4MR-M20-0.   MAC-4MR-M20-1.   MAC-4MR-M20-1.   MAC-4MR-M20-2.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-4.   MAC-4MR-M20-6.   MAC-4M	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   40" [1.0m]   40" [2.0m]   40   118" [3.0m]   40   118" [3.0m]   40   118" [3.0m]   40   1236" [6.0m]   ARE AVAILABLE   ULT FACTORY
HELL: CONTACTS: VIRES: VIRES: VO NSERT: D-RING: UT: NPPROVALS IS:	CLEAR ANODIZED ALU CLEAR ANODIZED ALU GOLD PLATED COPPEN STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC OLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRASS S UL LISTED	R ALLOY [7.6	14.9	1.0		DIMENSIONS ARE IN INCHES	DRAWN DATE 08/ CHECKED BY	MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1 MAC-4MR-M20-2 MAC-4MR-M20-3 MAC-4MR-M20-3 MAC-4MR-M20-4 MAC-4MR-M20-5 MAC-4MR-M20-6 MAC-	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   40" [2.0m]   40" [3.0m]   418" [3.0m]   4157" [4.0m]   4193" [5.0m]   4193" [5.0m]   4193" [5.0m]   ARE AVAILABLE   ULT FACTORY   ORPORATION
SHELL: CONTACTS: WIRES: V( NSERT: D-RING: IUT: APPROVALS JS: CANADA:	CLEAR ANODIZED ALU CLEAR ANODIZED ALU GOLD PLATED COPPER STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC OLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRASS UL LISTED C-UL LISTED	R ALLOY [7.6	14.9			DIMENSIONS ARE IN INCHES	DRAWN DATE 08/ CHECKED BY	MAC-4MR-M20-0.   MAC-4MR-M20-0.   MAC-4MR-M20-0.   MAC-4MR-M20-1.   MAC-4MR-M20-1.   MAC-4MR-M20-2.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-4.   MAC-4MR-M20-5.   MAC-4MR-M20-6.   OTHER LENGTHS PLEASE CONST   ADM (04/2023 JJH   JJH   TITLE:	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   40" [2.0m]   418" [3.0m]   4157" [4.0m]   4193" [5.0m]   4193" [5.0m]
SHELL: CONTACTS: WIRES: V( NSERT: D-RING: NUT: APPROVALS JS: CANADA: ROHS:	CLEAR ANODIZED ALU CLEAR ANODIZED ALU GOLD PLATED COPPER STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC OLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRASS UL LISTED C-UL LISTED YES	R ALLOY [7.6	14.9   .59	VOLTS	300V	DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 08/ CHECKED BY	MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1M MAC-4MR-M20-2M MAC-4MR-M20-3M MAC-4MR-M20-3M MAC-4MR-M20-3M MAC-4MR-M20-5M MAC-4MR-M20-6M OTHER LENGTHS PLEASE CONST MAC-4MR-M20-6M OTHER LENGTHS PLEASE CONST MAC-4MR-M20-6M OTHER LENGTHS PLEASE CONST MAC-4MR-M20-6M OTHER LENGTHS PLEASE CONST MAC-4MR-M20-6M OTHER LENGTHS PLEASE CONST MAC-4MR-M20-6M MAC-4MR-M20-6M MAC-4MR-M20-3M MAC-4MR-M20-5M MAC-4MR-M20-5M MAC-4MR-M20-6	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   40" [2.0m]   40" [3.0m]   418" [3.0m]   4157" [4.0m]   4193" [5.0m]   4193" [5.0m]   4193" [5.0m]   4193" [5.0m]   ARE AVAILABLE   ULT FACTORY   ORPORATION   C M20 RCP
SHELL: CONTACTS: WIRES: V(	CLEAR ANODIZED ALU CLEAR ANODIZED ALU GOLD PLATED COPPER STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC OLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRASS UL LISTED C-UL LISTED YES	R ALLOY [7.6	PROPRIETARY AND CONFIDENTIAL   THE INFORMATION CONTINUED IN THIS   DRAWING IS THE SOLE PROPERTY OF		300V 4A	DIMENSIONS ARE IN INCHES AND [MM] MATERIAL	DRAWN DATE 08/ CHECKED BY CHECK DATE 08/	MAC-4MR-M20-0.   MAC-4MR-M20-0.   MAC-4MR-M20-1.   MAC-4MR-M20-1.   MAC-4MR-M20-2.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-3.   MAC-4MR-M20-6.   MAC-4MR-M20-6.   MAC-4MR-M20-6.   OTHER LENGTHS PLEASE CONST   ADM   MAC-4MR-M20-6.   OTHER LENGTHS PLEASE CONST   ADM   MENCOM CO   JJH   TITLE:   6 PL ML MA   SIZE DWG. NO.	5M 20" [0.5m]   6M 24" [0.6m]   40" [1.0m]   40" [1.0m]   40" [1.0m]   40" [1.0m]   40" [2.0m]   4118" [3.0m]   4193" [5.0m]   ARE AVAILABLE   ULT FACTORY   ORPORATION   C M20 RCP   REV
SHELL: CONTACTS: WIRES: V( NSERT: D-RING: NUT: APPROVALS US: CANADA: ROHS:	CLEAR ANODIZED ALU CLEAR ANODIZED ALU GOLD PLATED COPPER STYLE: UL 1007/1569 AWG: 22 AWG JACKET: PVC OLTAGE: 300V POLYAMIDE NBR NICKEL PLATED BRASS UL LISTED C-UL LISTED YES	R ALLOY [7.6	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	VOLTS		DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 08/ CHECKED BY CHECK DATE 08/	MAC-4MR-M20-0. MAC-4MR-M20-0. MAC-4MR-M20-1M MAC-4MR-M20-2M MAC-4MR-M20-3M MAC-4MR-M20-3M MAC-4MR-M20-3M MAC-4MR-M20-5M MAC-4MR-M20-6M OTHER LENGTHS PLEASE CONST ADM MENCOM CO MENCOM CO 11TLE: 6 PL ML MA	5M 20" [0.5m]   6M 24" [0.6m]   6M 40" [1.0m]   V 79" [2.0m]   V 118" [3.0m]   V 157" [4.0m]   V 193" [5.0m]   V 236" [6.0m]   ARE AVAILABLE ULT FACTORY   DRPORATION   C M20 RCP