



REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	REDRAWN IN NEW CAD	12/2/2004	BEM
B	ADDED TAB;ES	6/1/2006	

SPECIFICATIONS:	Ⓑ
TIGHTENING TORQUE:	10 Nm
TEMPERATURE:	-20°C - +100°C

MATERIALS:	
BODY:	NICKEL PLATED BRASS
INSERT:	POLYAMIDE
GROMMET:	NEOPRENE
LOCK NUT:	NICKEL PLATED BRASS
O-RING:	BUNA-N

SEAL RATED TO: IP 68

LOCK NUT INCLUDED BUT NOT SHOWN

PART NUMBER	SEALING RANGE
Ⓑ MCG-21	.512 - .709 [13 - 18 mm]
MCG-21R	.354 - .630 [9 - 16 mm]

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME
DIMENSIONS ARE IN INCHES AND [MM]		BEM
		DRAWN
		CHECKED
		ENG APPR.
		MFG APPR.
		Q.A.
		COMMENTS:
MATERIAL		
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION			
TITLE:			
SIZE	DWG. NO.	REV	
B	MCG-21	B	
SCALE: 3:1	WEIGHT:	SHEET 1 OF 1	