



REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	REDRAWN IN NEW CAD	1/12/2005	
B	ADDED TABLE	6/1/2006	

LOCK NUT INCLUDED BUT NOT SHOWN

SEAL RATED TO: IP68

SPECIFICATIONS:	Ⓑ
TIGHTENING TORQUE:	7.5 Nm
TEMPERATURE:	-20°C - +100°C

PART NUMBER	SEALING RANGE
MCGB-16	0.394" - 0.551" [10-14MM]
MCGB-16R	0.276" - 0.472" [7 - 12MM]

MATERIALS:	
BODY:	NICKEL PLATED BRASS
INSERT:	POLYAMIDE
GROMMET:	NEOPRENE
LOCK NUT:	NICKEL PLATED BRASS
O-RING:	BUNA-N

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME
DIMENSIONS ARE IN INCHES		BEM
		DRAWN
		CHECKED
		ENG APPR.
		MFG APPR.
		Q.A.
		COMMENTS:
MATERIAL		
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION		
TITLE:		
PG16 METAL CABLE GLAND		
SIZE	DWG. NO.	REV
B	MCGB-16	B
SCALE: 3:1	WEIGHT:	SHEET 1 OF 1