	8	7	6	5	4	3	I
PIN #	¢ COLO	R					· · · · · · · · · · · · · · · · · · ·
1	BROW	Ν					
2	N/A						
3	BLUE						
4	BLAC	٢					
			4 4] [44]				
	Not a second	and the					
						B	
	M						
	RAAD.	A CONTRACTOR OF THE OWNER OWNER OF THE OWNER OF THE OWNER		[5]			
				[5] Ø.20			
		15]	∕M12x1	ψ .20			
_							
	¥	.0					
			-	L			
MATERIA	15					I	
BODY:		YELLOW PVC					
CONTAC		GOLD PLATED COPPER ALLOY					
CABLE:							
	STYLE:						
		22 AWG	_				
	JACKET:	YELLOW PVC					
	JACKET: VOLTAGE:	YELLOW PVC 600V					
	JACKET: VOLTAGE: SHIELD:	YELLOW PVC 600V NO					
COUPLIN	JACKET: VOLTAGE: SHIELD:	YELLOW PVC 600V NO NICKEL PLATED BRASS					
COUPLIN INSERT:	JACKET: VOLTAGE: SHIELD: IG:	YELLOW PVC 600V NO NICKEL PLATED BRASS POLYAMIDE				LINI ESS OTHERWISE SPECIFIED	
COUPLIN	JACKET: VOLTAGE: SHIELD: IG:	YELLOW PVC 600V NO NICKEL PLATED BRASS				UNLESS OTHERWISE SPECIFIED:	
COUPLIN INSERT: O-RING:	JACKET: VOLTAGE: SHIELD: IG:	YELLOW PVC 600V NO NICKEL PLATED BRASS POLYAMIDE				UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY DRAWN DATE CHECKED BY
COUPLIN INSERT: O-RING: APPROVA	JACKET: VOLTAGE: SHIELD: IG: ALS	YELLOW PVC 600V NO NICKEL PLATED BRASS POLYAMIDE N/A				DIMENSIONS ARE IN INCHES	DRAWN DATE
COUPLIN INSERT: O-RING: APPROVA US:	JACKET: VOLTAGE: SHIELD: IG: ALS	YELLOW PVC 600V NO NICKEL PLATED BRASS POLYAMIDE				DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY
COUPLIN INSERT: O-RING: APPROVA	JACKET: VOLTAGE: SHIELD: IG: ALS	YELLOW PVC 600V NO NICKEL PLATED BRASS POLYAMIDE N/A			VOITS 200V	DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY
COUPLIN INSERT: O-RING: APPROVA US: CANADA	JACKET: VOLTAGE: SHIELD: IG: ALS	YELLOW PVC 600V NO NICKEL PLATED BRASS POLYAMIDE N/A UL LISTED C-UL LISTED		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	VOLTS 300V AMPS 4A	DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY
COUPLIN INSERT: O-RING: APPROVA US: CANADA ROHS:	JACKET: VOLTAGE: SHIELD: IG: ALS	YELLOW PVC 600V NO NICKEL PLATED BRASS POLYAMIDE N/A UL LISTED C-UL LISTED YES		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	AMPS 4A	DIMENSIONS ARE IN INCHES AND [MM] MATERIAL	DRAWN DATE CHECKED BY CHECK DATE
COUPLIN INSERT: O-RING: APPROVA US: CANADA ROHS: CE & UKC RATINGS	JACKET: VOLTAGE: SHIELD: IG: ALS A: CA:	YELLOW PVC 600V NO NICKEL PLATED BRASS POLYAMIDE N/A UL LISTED C-UL LISTED YES		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF		DIMENSIONS ARE IN INCHES AND [MM] MATERIAL	DRAWN DATE CHECKED BY CHECK DATE

MDC	-3MP-5N	I	197" [5m	י] [י	YES	-				
MDC	-3MP-6N	1	236" [6m	n]	NO					
MDC	-3MP-8N	1	315" [8m]	NO					
MDC	-3MP-10	Μ	393" [10n	n]	YES	В				
MDC	-3MP-15	Μ	591" [15n	n]	YES					
MDC	-3MP-20	Μ	787" [20n	n]	NO					
MDC	-3MP-30	Μ	1181" [30	m]	NO					
MDC	-3MP-50	Μ	1968" [50	m]	NO					
PARTS LISTED AS NOT BEING STANDARD MAY HAVE MINIMUM ORDER QUANTITIES										
ADM MENCOM CORPORATION										
JJH TITLE:										
3 PL MALE MDC PLG 22AWG										
SIZE DWG. NO.						-				
B MDC-3MP-ZZ										
	SCALE: 3:2	WEIGH	HT:	SHEE	T 1 OF 1					
	2			1						

1

P/N

MDC-3MP-1M

MDC-3MP-2M

MDC-3MP-3M

MDC-3MP-4M

С

STD?

YES

YES

YES

YES

L

40" [1m]

79" [2m]

118" [3m]

157" [4m]