8		7	6		5	+	4	3	
D		[2 .8	1] 3		-		[38] 1.5		
								 	40]
С	[22]_ Ø.9			─_M12X1				1	1.6
MATERIALS	:								

	BODY:	POLYAMIDE
	COUPLING:	STAINLESS STEEL
	Contacts:	GOLD PLATED COPPER ALLOY
В	GROMMET:	NBR
	O-RING:	FPM
	specifications:	
	WIRE RANGE:	18-24AWG [1.0 - 0.25sqmm]
	CABLE RANGE:	0.118 - 0.255 [3 - 6.5mm]
	CONNECTION:	SCREW TERMINALS
	VOLTS:	250∨
	AMPS:	4A
	SEAL:	IP67

А

	,
APPROVALS:	
US:	UL RECOGNIZED
CANADA:	C-UL RECOGNIZED
8	7

		UNLESS OTHERWISE SPECIFIED:		NAME				
		AND [MM]	DRAWN	DCT	MENCOM CORPORATION			
	AND [MM]		CHECKED					
		ENG APPR.						
			MFG APPR.					
PROPRIETARY AND CONFIDENTIAL			Q.A.		_			
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION, ANY	TAINED IN THIS ROPERTY OF	MATERIAL	COMMENTS:		SIZE DWG. NO.			REV ▲
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS		FINISH			B MDC-4F	P-FW07-R-S	22	A
PROHIBITED.		DO NOT SCALE DRAWING			SCALE: 2:1 WEIGHT:		SHEET 1	OF 1
5	4	3			2		1	

6

	2	1	
	REVISIONS		
REV.	DESCRIPTION	DATE	APPROVED
А	REDRAWN IN SW	11/14/12	

D

С

В