



WIRES ARE TERMINATED VIA
SCREW TERMINALS

B	MATERIALS	
	BODY:	BLACK POLYAMIDE
	CONTACTS:	GOLD PLATED COPPER ALLOY
	COUPLING:	STAINLESS STEEL
	INSERT:	POLYAMIDE
	SEALS:	FPM & NBR
	GLAND SEAL	NBR
	SPECIFICATIONS:	
A	RATED CURRENT (A)	4A MAX
	RATED VOLTAGE (V)	250V MAX
	MAX WIRE SIZE:	18AWG
	MIN WIRE SIZE:	24AWG
	CABLE GRIP RANGE:	.157 - .315" [4mm - 8mm]
	TEMP RATING:	-13°F - 185°F [-25°C - 85°C]
	PROTECTION:	NEMA 1, 3, 4, 6P IEC IP67
	APPROVALS:	
	US	UL LISTED
	CANADA	C-UL LISTED
	RoHS:	YES
	CE:	YES

Voltage rating is 250V or the
rating of the cable, whichever
is less.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	GO	MENCOM CORPORATION		
	DRAWN DATE	11/05/2020			
	CHECKED BY	GO	TITLE: 4 POLE R/A FEM M12 FIELD WIREABLE CONNECTOR		
	CHECK DATE	11/06/2020			
MATERIAL	COMMENTS:		SIZE	DWG. NO.	REV
FINISH			B	MDC-4FP-FW09-R-SS	A
DO NOT SCALE DRAWING			SCALE: 2:1	WEIGHT:	SHEET 1 OF 1