		8	7		6	5	4		3		2	1	
	PIN #	COLOR											
	1	BROWN											
		WHITE											
		BLUE											
	4	BLACK											
-		√  4]  6 	-M12x1 Female Thread		[45] 1.8		 [5.0] Ø.20			MDC-4	4FP-1M-SS 4FP-2M-SS 4FP-3M-SS 4FP-4M-SS	L 40" [1M] 79" [2M] 118" [3M] 157" [4M]	STD? YES YES NO YES
										MDC-4	4FP-5M-SS	197" [5M]	YES
	AATERIALS									MDC-	4FP-6M-SS	236" [6M]	NO
	ODY: YELLOW PVC CONTACTS: GOLD PLATED COPPER ALLOY		.OY						MDC-4	4FP-8M-SS	315" [8M]	NO	
CA	CABLE:								MDC-4	4FP-10M-SS	393" [10M]	YES	
		STYLE: AWM AWG: 22/4											
		JACKET: YELLO	OW PVC								4FP-15M-SS	590" [15M]	
	VOLTAGE: 600V SHIELD: NO								MDC-4	4FP-20M-SS	786" [20M]	NO	
С	COUPLING: STAINLESS STEEL										RTS LISTED AS NC Y HAVE MINIMUN		
	SERT:		AMIDE						UNLESS OTHERWISE SPECIFIED				NIIILS
	-RING:	FPM							DIMENSIONS ARE IN INCHES	DRAWN BY ADM   DRAWN DATE 08/05/2021	MENCOM	CORPORA	TION
	PPROVALS								AND [MM]	CHECKED BY JJH	TITLE:		
US: UL LISTED									CHECK DATE 08/05/2021	4 PL N	DC FEM PL	G	
	CANADA: C-UL LISTED ROHS: YES							0001					-
CE		YES				PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	VOLTS AMPS	300∨ 4A	MATERIAL	COMMENTS:			
						DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY				_	SIZE DWG. NO.		REV
	ATINGS					REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS	TEMP:	105°C				C-4FP-ZZ-SS	B
PR	ROTECTION	N CLASS: UL TY	PE 4 & 12, IEC IP69			PROHIBITED.			DO NOT SCALE DRAWING		SCALE: 3:2 WEIGHT	:	HEET 1 OF 1