



MATERIALS	
SHELL:	CLEAR ANODIZED ALUMINUM
CONTACTS:	GOLD PLATED COPPER ALLOY
INSERT:	POLYAMIDE
O-RING:	NBR
NUT:	ZINC PLATED STEEL

APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED
ROHS:	YES
CE & UKCA:	YES

RATINGS	
PROTECTION CLASS:	UL TYPE 4 & 12, IEC IP69

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

VOLTS	300V max
AMPS	4A max
TEMP:	105°C

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
AND [MM]
DRAWN BY: ADM
DRAWN DATE: 07/07/2023
CHECKED BY: JJH
CHECK DATE: 07/07/2023
COMMENTS:
MATERIAL
FINISH
DO NOT SCALE DRAWING

MENCOM CORPORATION

SIZE	DWG. NO.	REV
B	MDC-4MR-2-SC	B
SCALE: 3:1	WEIGHT:	SHEET 1 OF 1