	8	7	I	6	5	4		3	1		2	1
PIN #	COLO	2										
1												
-	BROW											
2	WHITE											
3	BLUE											
4	BLACK	< label{eq:started_startes_started_startes										
				M12x1-		/1/4-18	- L NPT					
		[17] .67	-									
		.07									P/N	L
					[13]	_ [8.5] .33					MDC-4MR-4-SS	12" [0.3m]
					.51	.33					MDC-4MR-4-0.5M-SS	20" [0.5m]
											MDC-4MR-4-0.6M-SS	24" [0.6m]
										-	MDC-4MR-4-1M-SS	40" [1m]
MATERIALS			]								MDC-4MR-4-2M-SS	79" [2m]
SHELL:		TAINLESS STEEL	-								MDC-4MR-4-3M-SS	118" [3m]
CONTACTS: WIRES:	: 0	GOLD PLATED COPPER ALLOY	-								MDC-4MR-4-4M-SS	157" [4m]
		JL 1007/1569	-								MDC-4MR-4-5M-SS	197" [5m]
	AWG: 2 JACKET: P		-							-	MDC-4MR-4-10M-SS	
	OLTAGE: 3		-									393" [10m]
INSERT:		OLYAMIDE	-								OTHER LENGTHS AVAI	
O-RING: NUT:		NBR INC PLATED STEEL	-					UNLESS OTHERWISE SPECIFIED	).		CONSULT FAC	
NUI.	L		-					DIMENSIONS ARE IN INCHES		ADM 7/19/2023	MENCOM CORP	ORATION
APPROVALS			_					AND [MM]	CHECKED BY	JJH	TITLE:	
US:		JL LISTED	-						CHECK DATE 07	7/20/2023	4 PL 1/4'' NPT N	ADC MI
		C-UL LISTED	-								RECP	
	N N	(ES			PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	VOLTS	300V		COMMENTS:			1
ROHS:		/FS	1		DRAWING IS THE SOLE PROPERTY OF	AMPS	4A	MATERIAL			SIZE DWG. NO.	REV
ROHS:		/ES	-				4/\					<b>P</b>
CANADA: ROHS: CE & UKCA: RATINGS		(ES	-		MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS	TEMP:	105°C	FINISH			<b>B</b> MDC-4MR-4-7	ZZ-SS <b>B</b>