



REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	Redrawn	9/6/2007	
B	UL & SPECS CHANGED	11/10/2014	JJH

MATERIALS:	
BODY:	POLYAMIDE
COUPLING:	NICKEL PLATED ZINC
CONTACTS:	GOLD PLATED COPPER ALLOY
GROMMET:	NBR
O-RINGS:	NBR & FPM
SPECIFICATIONS:	
WIRE RANGE:	18-24AWG [1.0 - 0.25sqmm]
CABLE RANGE:	0.118 - 0.255 [3.0 - 6.5mm]
CONNECTION:	SCREW TERMINALS
VOLTS:	125V
AMPS:	4A
SEAL:	IP67
TEMP RANGE:	STATIC: -40°C - +100°C
	DYNAMIC: -20°C -+100°C

APPROVALS:	
US:	UL LISTED
CANADA:	C-UL LISTED

All connections made via Screw Terminals.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]		NAME	MENCOM CORPORATION		
	MATERIAL	DRAWN			
	FINISH	CHECKED			
		ENG APPR.			
		MFG APPR.			
		Q.A.			
		COMMENTS:	TITLE:		
			SIZE	DWG. NO.	REV
			B	MDC-5FP-FW07-R	B
			SCALE: 2:1	WEIGHT:	SHEET 1 OF 1