APPROVALS		M12x1 FEMALE THREAD					[64] 2.5	
BODY: POLYAMIDE CONTACTS: GOLD PLATED COPPER ALLOY COUPLING: NICKEL PLATED BRASS INSERT: POLYAMIDE GROMMET: FPM SPECIFICATIONS WIRE RANGE: 18-24AWG [1.0 - 0.25 sqmm] CABLE RANGE: 0.197-0.393 [5.0 - 10.0mm] CONNECTION: SCREW TERMINALS MUNUESS OTHERWISE SPECIFIED: punetsions are in inches and inches and inches are in inches and inches and inches are in inches and inches and inches and inches are in inches and inches and inches and inches are in inches and inches and inches and inches and inches and inches are in inches and inches and inches and inches are in inches and inches and inches and inches and inches and inches are in inches and inches and inches and inches are in inches and inches are in inches and inches are in inches and inches and inches are in inches and inches and inches are in inches and inches are in inches are in inches are in inches are in inches are inches and inches are inches are inches and inches are inches are inches are inches and inches are in			[21]					
COUPLING: NICKEL PLATED BRASS INSERT: POLYAMIDE GROMMET: FPM SPECIFICATIONS WIRE RANGE: 18-24AWG [1.0 - 0.25 sqmm] CABLE RANGE: 0.197-0.393 [5.0 - 10.0mm] CONNECTION: SCREW TERMINALS MIRENGINS ARE IN INCHES MILESS OTHERWISE SPECIFIED: APPROVALS Image: Marcine Mar	BODY:							
INSERT: POLYAMIDE GROMMET: FPM SPECIFICATIONS SPECIFICATIONS WIRE RANGE: 18-24AWG [1.0 - 0.25 sqmm] CABLE RANGE: 0.197-0.393 [5.0 - 10.0mm] CONNECTION: SCREW TERMINALS DIMENSIONS ARE IN INCHES DIMENSIONS ARE IN INCHES APPROVALS Image: Constant of the second			_					
GROMMET: FPM GROMMET: FPM SPECIFICATIONS Image: Specifications WIRE RANGE: 18-24AWG [1.0 - 0.25 sqmm] CABLE RANGE: 0.197-0.393 [5.0 - 10.0mm] CONNECTION: SCREW TERMINALS DIMENSIONS ARE IN INCHES pressions are in inches and indicate and inches and	COUPLING:		-					
SPECIFICATIONS SPECIFICATIONS WIRE RANGE: 18-24AWG [1.0 - 0.25 sqmm] CABLE RANGE: 0.197-0.393 [5.0 - 10.0mm] CONNECTION: SCREW TERMINALS UNLESS OTHERWISE SPECIFIED: provide and	INICEDT		-					
WIRE RANGE: 18-24AWG [1.0 - 0.25 sqmm] CABLE RANGE: 0.197-0.393 [5.0 - 10.0mm] CONNECTION: SCREW TERMINALS DIMENSIONS ARE IN INCHES AND [MM] DIMENSIONS ARE IN INCHES AND [MM]		rr <i>i</i> m	_					
CABLE RANGE: 0.197-0.393 [5.0 - 10.0mm] CONNECTION: SCREW TERMINALS UNLESS OTHERWISE SPECIFIES IMENSIONS ARE IN INCHES APPROVALS Imensions are in inches		rr <i>m</i>						
CONNECTION: SCREW TERMINALS UNLESS OTHERWISE SPECIFIED: DM DIMENSIONS ARE IN INCHESS DM DM DM APPROVALS Image: Comparison of the com	GROMMET:		_					
APPROVALS	GROMMET: SPECIFICATIONS		_					
APPROVALS AND [MM]	GROMMET: SPECIFICATIONS WIRE RANGE:	18-24AWG [1.0 - 0.25 sqmm] 0.197-0.393 [5.0 - 10.0mm]						
APPROVALS	GROMMET: SPECIFICATIONS WIRE RANGE: CABLE RANGE:	18-24AWG [1.0 - 0.25 sqmm] 0.197-0.393 [5.0 - 10.0mm]					UNLESS OTHERWISE SPECIFIED:	DRA
	GROMMET: SPECIFICATIONS WIRE RANGE: CABLE RANGE:	18-24AWG [1.0 - 0.25 sqmm] 0.197-0.393 [5.0 - 10.0mm]					DIMENSIONS ARE IN INCHES	DRA DRA
	GROMMET: SPECIFICATIONS WIRE RANGE: CABLE RANGE: CONNECTION: APPROVALS	18-24AWG [1.0 - 0.25 sqmm] 0.197-0.393 [5.0 - 10.0mm] SCREW TERMINALS					DIMENSIONS ARE IN INCHES	DRA
	GROMMET: SPECIFICATIONS WIRE RANGE: CABLE RANGE: CONNECTION: APPROVALS US:	18-24AWG [1.0 - 0.25 sqmm] 0.197-0.393 [5.0 - 10.0mm] SCREW TERMINALS					DIMENSIONS ARE IN INCHES	DRA
	GROMMET: SPECIFICATIONS WIRE RANGE: CABLE RANGE: CONNECTION: APPROVALS US: CANADA:	18-24AWG [1.0 - 0.25 sqmm] 0.197-0.393 [5.0 - 10.0mm] SCREW TERMINALS UL LISTED C-UL LISTED					DIMENSIONS ARE IN INCHES	DRA
	GROMMET: SPECIFICATIONS WIRE RANGE: CABLE RANGE: CONNECTION: APPROVALS US: CANADA: ROHS:	18-24AWG [1.0 - 0.25 sqmm] 0.197-0.393 [5.0 - 10.0mm] SCREW TERMINALS UL LISTED C-UL LISTED YES		PROPRIETARY AND CONFIDENTIAL	VOLTS	250∨	DIMENSIONS ARE IN INCHES	DRA CHE
	GROMMET: SPECIFICATIONS WIRE RANGE: CABLE RANGE: CONNECTION: APPROVALS US: CANADA: ROHS:	18-24AWG [1.0 - 0.25 sqmm] 0.197-0.393 [5.0 - 10.0mm] SCREW TERMINALS UL LISTED C-UL LISTED YES		THE INFORMATION CONTAINED IN THIS			DIMENSIONS ARE IN INCHES AND [MM]	DRA
MENCOM CORPORATION. ANY MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TEMP: 105°C	GROMMET: SPECIFICATIONS WIRE RANGE: CABLE RANGE: CONNECTION: APPROVALS US: CANADA: ROHS: CE:	18-24AWG [1.0 - 0.25 sqmm] 0.197-0.393 [5.0 - 10.0mm] SCREW TERMINALS UL LISTED C-UL LISTED YES		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION, ANY	AMPS	4A	DIMENSIONS ARE IN INCHES AND [MM] MATERIAL	DRA CHE

6

7

8

5

Ļ

4



THERWISE SPECIFIED:	THERWISE SPECIFIED: DRAWN BY ADM			MENCOM CORPORATION					
NS ARE IN INCHES]	DRAWN DATE	09/22/2016	I		COMCORFORATION				
	CHECKED BY		TITLE	≣:					
	CHECK DATE			<i>–</i> –					A
				5 F		IELD WIRE			
	-			FEM, PG11					
	COMMENTS:								
			SIZE DWG. NO.				REV		
	-		В		MDC	-5FP-FW1	1	Α	
DT SCALE DRAWING			SCALE: 2:1		WEIGHT	:	SHEET	1 OF 1	
3			2				1		-

D

С