8		7	6	5	4		3		2	1
PIN # CC	OLOR					_				
							REV.	DESCRIPTIO		APPROVED
	ROWN									
2 WI	HITE									
3 BL	UE									
4 BL	ACK									
5 GF	RAY									
			-M12x1 FEMALE THREAD							
<b>A</b>	/		-	1/2-14 NPT	— L ——					
[25.4 1.0				1/2-14 NF1						
					×	> <u>&gt;</u>		_		
Ţ									P/N	L
									MDC-5FR-2-18	12" [0.3m]
									MDC-5FR-2-0.5M-18	19" [0.5m]
			[15.3]	[11.4]					MDC-5FR-2-1M-18	40" [1m]
			.60	.45					MDC-5FR-2-2M-18	79" [2m]
MATERIALS							←ED		MDC-5FR-2-3M-18	118" [3m]
BODY:		ED ALUMINUM		CLUDED ON LENGTHS			JLN		MDC-5FR-2-4M-18	
CONTACTS:	GOLD PL	ATED COPPER ALLOY								157" [4m]
WIRES: INSERT:	18AWG POLYAM	JL1007/1569					UNLESS OTHERWISE SPECIFIED	).	MDC-5FR-2-5M-18	197" [5m]
O-RINGS: NBR & FPM		DIMENSIONS ARE IN INCHES DRAWN								
LOCKNUT:	ZINC PL	ATED STEEL					AND [MM]	CHECKED ENG APPR.	TITLE:	
APPROVALS:								MFG APPR.		
US CANADA		UL LISTED C-UL LISTED		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	VOLTS AMPS	300∨ 4A	MATERIAL	Q.A. COMMENTS:	SIZE DWG. NO.	REV
				REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF	TEMP	105°C	FINISH		B MDC-5FR-2	-ZZ-18 A
		UL TYPE 4, 12, IEC IP67		MENCOM CORPORATION IS PROHIBITED.	SPECIFICA		DO NOT SCALE DRAWING		SCALE: 2:1 WEIGHT:	SHEET 1 OF 1