

PIN #	COLOR
1	BROWN
2	WHITE
3	BLUE
4	BLACK
5	GRAY

TABLE A	
P/N	L
MDC-5MR-2-18-SS	12" [0.3M]
MDC-5MR-2-0.5M-18-SS	20" [0.5M]
MDC-5MR-2-0.6M-18-SS	24" [0.6M]
MDC-5MR-2-1M-18-SS	40" [1M]
MDC-5MR-2-2M-18-SS	79" [2M]
MDC-5MR-2-3M-18-SS	118" [3M]
MDC-5MR-2-4M-18-SS	157" [4M]
MDC-5MR-2-5M-18-SS	197" [5M]
MDC-5MR-2-10M-18-SS	393" [10M]

OTHER LENGTHS ARE AVAILABLE
PLEASE CONSULT FACTORY

UNLESS OTHERWISE SPECIFIED:		DRAWN BY	ADM
DIMENSIONS ARE IN INCHES AND [MM]		DRAWN DATE	07/07/2023
		CHECKED BY	JJH
		CHECK DATE	07/07/2023
		COMMENTS:	
MATERIAL			
FINISH			
DO NOT SCALE DRAWING			

VOLTS	300V
AMPS	4A
TEMP:	105°C

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A whole WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

SIZE	DWG. NO.	REV
B	MDC-5MR-2-ZZ-18-SS	B
SCALE: 2:1	WEIGHT:	SHEET 1 OF 1

MATERIALS	
SHELL:	STAINLESS STEEL
CONTACTS:	GOLD PLATED COPPER ALLOY
WIRES:	
STYLE:	UL 1007/1569
AWG:	18 AWG
JACKET:	PVC
VOLTAGE:	300V
INSERT:	POLYAMIDE
O-RING:	FPM
NUT:	ZINC PLATED STEEL

APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED
ROHS:	YES
CE & UKCA:	YES

RATINGS	
PROTECTION CLASS:	UL TYPE 4 & 12, IEC IP69