8		7	6	5	2	4	3	I	2	1	
PIN # C	OLOR										
1 B	ROWN										
	HITE										
				-		L					
5 G	RAY				<u> </u>	14NPT					
			M12x1								
<u> </u>	8					$\overline{\langle}$			BLE A		
						· · · ·					
								P/N			
									C-5MR-2-SS	40" 50M	Л Л
										12" [.3N	
									C-5MR-2-0.5M-SS	20" [.5N	
MATERIALS			[15.7] .62		[10.9] .43				C-5MR-2-0.6M-SS	24" [.6N	
SHELL: CONTACTS:	STAINLES GOLD PL	S STEEL ATED COPPER ALLOY	.02		.40			MD	C-5MR-2-1M-SS	40" [1M	1]
WIRES:		5/0						MD	C-5MR-2-2M-SS	79" [2M	[]
	STYLE: UL 1007/ AWG: 22 AWG	707						MD	C-5MR-2-5M-SS	197" [5N	/ 1
	CKET: PVC										
	AGE: 300V							MD	C-5MR-2-10M-SS OTHER LENGTHS A	393" [10]	
INSERT:	POLYAM	DE							PLEASE CONSULT		
							DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 07/11/	2023 MENCOM COR	PORATION	
APPROVALS US:	UL LISTED								DATE 07/12/2023		
CANADA:	C-UL LIST		5 PL SS MDC ML							C ML RECP	
ROHS:	YES				VOLTS	30011					
CE & UKCA:	YES			PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS		300∨	MATERIAL	COMMENTS:	SIZE DWG. NO.	וס	REV
	I			DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	AMPS	4A					
RATINGS		& 12, IEC IP69		REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS	TEMP:	105°C	FINISH DO NOT SCALE DRAWING	_	SCALE: 1:1 WEIGHT:	C-2-ZZ-SS	B
				PROHIBITED.							