			• · · · · · · · · · · · · · · · · · · ·	3		
	M12x1 FEMALE THREAD	-	[56] 2.2			
	[21]	WIRES ARE	E TERMINATED VIA	a screw term	INALS	
SPECIFICATIO	Ø.8					
SPECIFICATIO						
	NS:					
RATED CURRE RATED VOLTA	NS: ENT (A) 2A AGE (V) 60V					
RATED CURRE RATED VOLTA MAX WIRE SIZ	NS: ENT (A) 2A AGE (V) 60V Æ: 20AWG [0.5sqmm]					
RATED CURRE RATED VOLTA MAX WIRE SIZ MIN WIRE SIZE	NS: ENT (A) 2A AGE (V) 60V E: 20AWG [0.5sqmm] E: 26AWG [0.14sqmm]					
	NS: ENT (A) 2A AGE (V) 60V E: 20AWG [0.5sqmm] E: 26AWG [0.14sqmm] RANGE: .117256" [3 - 6.5mm]					
RATED CURRE RATED VOLTA MAX WIRE SIZ MIN WIRE SIZE CABLE GRIP R TEMP RATING:	NS: ENT (A) 2A AGE (V) 60V E: 20AWG [0.5sqmm] E: 26AWG [0.14sqmm] RANGE: .117256" [3 - 6.5mm]			UNLESS OTHERWISE SPECIFIE	BRATTER	HIL
RATED CURRE RATED VOLTA MAX WIRE SIZ MIN WIRE SIZE CABLE GRIP R TEMP RATING:	NS: ENT (A) 2A AGE (V) 60V E: 20AWG [0.5sqmm] E: 26AWG [0.14sqmm] RANGE: .117256" [3 - 6.5mm]			UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES AND [MM]	D: DRAWN BY DRAWN DATE CHECKED BY	JJH 09/07/2017 ADM
RATED CURRE RATED VOLTA MAX WIRE SIZ MIN WIRE SIZE CABLE GRIP R TEMP RATING: MATERIALS	NS: ENT (A) 2A AGE (V) 60V E: 20AWG [0.5sqmm] E: 26AWG [0.14sqmm] RANGE: .117256" [3 - 6.5mm] : -40°F - 185°F [-40°C - 85°C]			DIMENSIONS ARE IN INCHES	DRAWN DATE	09/07/2017
RATED CURRE RATED VOLTA MAX WIRE SIZ MIN WIRE SIZE CABLE GRIP R TEMP RATING: MATERIALS BODY:	NS: ENT (A) 2A AGE (V) 60V Æ: 20AWG [0.5sqmm] E: 26AWG [0.14sqmm] RANGE: .117256" [3 - 6.5mm] : -40°F - 185°F [-40°C - 85°C] BLACK POLYAMIDE			DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY	09/07/2017 ADM
RATED CURRE RATED VOLTA MAX WIRE SIZE MIN WIRE SIZE CABLE GRIP R TEMP RATING: MATERIALS BODY: CONTACTS:	NS: ENT (A) 2A AGE (V) 60V Æ: 20AWG [0.5sqmm] E: 26AWG [0.14sqmm] RANGE: .117256" [3 - 6.5mm] : -40°F - 185°F [-40°C - 85°C] BLACK POLYAMIDE GOLD PLATED COPPER ALLOY			DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE CHECKED BY	09/07/2017 ADM 09/07/2017
RATED CURRE RATED VOLTA MAX WIRE SIZE CABLE GRIP R TEMP RATING: MATERIALS BODY: CONTACTS: COUPLING:	NS: ENT (A) 2A AGE (V) 60V Æ: 20AWG [0.5sqmm] E: 26AWG [0.14sqmm] RANGE: .117256" [3 - 6.5mm] : -40°F - 185°F [-40°C - 85°C] BLACK POLYAMIDE GOLD PLATED COPPER ALLOY STAINLESS STEEL	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY		DIMENSIONS ARE IN INCHES AND [MM] MATERIAL	DRAWN DATE CHECKED BY CHECK DATE	09/07/2017 ADM 09/07/2017
RATED CURRE RATED VOLTA MAX WIRE SIZE MIN WIRE SIZE CABLE GRIP R TEMP RATING: MATERIALS BODY:	NS: ENT (A) 2A AGE (V) 60V Æ: 20AWG [0.5sqmm] E: 26AWG [0.14sqmm] RANGE: .117256" [3 - 6.5mm] : -40°F - 185°F [-40°C - 85°C] BLACK POLYAMIDE GOLD PLATED COPPER ALLOY	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF		DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE CHECKED BY CHECK DATE	09/07/2017 ADM 09/07/2017

JJH									
09/07/2017	MENCOM CORPORATION								
ADM	TITLE:								
09/07/2017								Α	
	SIZE	DWG.	NO.				REV		
	B MDC-8FP-FW07-SS								
	SCAL	E: 2:1	WEIGH	T:		SHEET	1 OF 1		
	2					1		1	

D

С

В