	8	7	6	5	4	3]
M12x1. FEMAL THREA[E	[14 .5	4.0] 55	[10.0] .39	Rec Rec	commended I commended I	MAX PCB 1
		[16.0] .63		[0.8] Ø.03		_[2.6] ∅.10	
[8.5] .33	[19.3]			[2.0]∕ ∅.08		_ [6.5] .26	
	[19.3] .76			[2.6] .10			[2.4] Ø.09
CONTACTS:	POLYAMIDE R: NICKEL PLATED B GOLD PLATED CO		_ 0				
O-RING:	FPM & NBR					UNLESS OTHERWISE SPECIFIED:	DRAWN BY
RATINGS:						DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE CHECKED BY
	60)/						CHECK DATE
VOLTAGE: AMPERAGE:	60V 2A						_
APPROVALS	8:				PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	MATERIAL	COMMENTS
					DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOL	LE FINISH	_
US	UL LISTED				WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS		

